

Roof Coatings | Roof Surfacing

Pyramic[®] Plus LO

Specifically engineered to preserve asphaltic modified bitumen systems, this water-based coating shields the roof from damaging UV rays and significantly lowers surface temperatures. By minimizing the thermal expansion and contraction cycles that lead to system fatigue, Pyramic Plus LO protects structural integrity while delivering substantial energy savings.



Extends Roof Longevity

- Reflects UV radiation to prevent premature roof failure
- Lowers surface temperatures, reducing material fatigue
- Acrylic-urethane blend ensures flexibility and durability



Superior Building Protection

- Delivers a high 104 SRI for maximum heat rejection
- Integrated biocides prevent mold and fungal growth
- Achieves Class A fire rating for enhanced safety



Occupant & Installer Friendly Application

- Non-toxic, low-odor formula ideal for sensitive environments
- Dual colors ensure uniform coverage during installation
- Eco-friendly formula meets strict global regulatory standards



Extends longevity by reducing thermal stress.

Highly reflective, antimicrobial protection.

Safe, low-odor coatings and global compliance.



The Garland Company, Inc.

3800 East 91st Street, Cleveland, OH 44105

Phone: 216-641-7500 | Toll Free: 800-321-9336 | Fax: 216-641-0633

www.garlandco.com

0226 ©2026 The Garland Company, Inc.

Pyramic[®] Plus LO

Features & Benefits

Proven System Longevity

Deflects aggressive solar radiation

The high-reflectance white finish blocks UV rays that otherwise cause asphaltic systems to degrade and fail prematurely.

Helps prevent damaging thermal expansion

By regulating surface temperatures, Pyramic Plus LO helps to prevent the repeated expansion and contraction cycles that fatigue roofing materials.

Superior Energy Performance

Lowers peak cooling demands

Reflecting solar energy reduces roof temperatures by up to 80°F (26.7°C), significantly easing the operational load on HVAC equipment.

Maintains clean reflective surfaces

Advanced biocides in the formula inhibit the growth of mold and algae to preserve the system's heat-rejecting properties.

Safe, Installer Focused Application

Protects sensitive environments

A low-odor, non-toxic formula allows for safe installation without disrupting building occupants or daily operations.

Uniform coverage thickness

The two opposing base and top coat colors provide installers a clear visual guide for consistent application.



Pyramic Plus LO

**Shields Roof,
Saves Energy**

Advantages of Pyramic Plus LO



Easy Application



Extends Roof Life



Protects Against UV
Damage



Boosts Energy Efficiency



Enhances Appearance



The Garland Company, Inc.

3800 East 91st Street, Cleveland, OH 44105

Phone: 216-641-7500 | Toll Free: 800-321-9336 | Fax: 216-641-0633

www.garlandco.com

0226 ©2026 The Garland Company, Inc.