

# SAFETY DATA SHEET

PRODUCT CODE: 2304

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Oil-Stop Primer Part A  
**PRODUCT CODES:** 2304

**MANUFACTURER:** The Garland Company, Inc.  
**STREET ADDRESS:** 3800 East 91<sup>st</sup>. Street  
**CITY, STATE, ZIP:** Cleveland, Ohio 44105

The Garland Company, Inc.  
209 Carrier Drive  
Toronto, Ontario M9W 5Y8



**INFORMATION PHONE:** 800-762-8225  
**EMERGENCY PHONE:** Chemtrec 800-262-8200

**PREPARED BY:** Bill Belardo

**DATE REVISED:** 05-26-15

**Chemical Name or Class:** Epoxy/Solvent mixture

## SECTION 2: HAZARDS IDENTIFICATION

### Hazard Overview

**GHS Classification:** Flammable liquid category 3, Specific target organ toxicity following repeated exposure category 2, Specific target organ toxicity – single exposure category 3, Aspiration hazard category 2, Acute dermal toxicity category 4, Skin corrosion/irritation category 2, skin sensitizer category 1B, Serious eye irritation category 2, Acute toxicity inhalation category 4, Chronic hazard to aquatic environment category 2

### GHS Label Elements and Precautionary Statements:

**Label Elements:** Flame, Health hazard, Exclamation Mark



### Hazard Statements:

Warning: Flammable liquid and vapor.

Warning: May cause damage to organs (auditory system) through prolonged or repeated exposure

Warning: may cause drowsiness or dizziness

Warning: May be harmful if swallowed and enters airways

Warning: Harmful in contact with skin

Warning: Causes skin irritation

Warning: May cause an allergic skin reaction

Warning: Causes serious eye irritation.

Warning: Harmful if inhaled

Toxic to aquatic life with long lasting effects.

Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P260 Do not breathe dust/fume/gas/mist/vapours/spray

P264 Wash skin thoroughly after handling.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P271 Use only outdoors or in a well-ventilated area

Response

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P370 + P378 In case of fire: Use FOAM, ALCOHOL FOAM, CO<sub>2</sub>, DRY CHEMICAL for extinction.

P314 Get medical advice/attention if you feel unwell

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 Do NOT induce vomiting.

P302 + P352 IF ON SKIN: wash with plenty of soap and water

P312 Call a POISON CENTER or doctor/physician if you feel unwell

P361+P364 Take off immediately all contaminated clothing and wash it before reuse.

# SAFETY DATA SHEET

PRODUCT CODE: 2304

P302 + P352 IF ON SKIN: wash with plenty of soap and water.

P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 IF eye irritation persists: Get medical advice/attention.

P273 Avoid release to the environment

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool

P405 Store locked up.

P233 Keep container tightly closed.

Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

Other Non-classifiable potential hazards

Carcinogenicity category 2, (Ethyl benzene at less than 17% in a study done by the NTP was determined to not be carcinogenic.)

## HMIS HAZARD CLASSIFICATION

HEALTH: 2 FLAMMABILITY: 3 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: G

## POTENTIAL HEALTH EFFECTS

### EYES:

CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING, OR BLURRED VISION

### SKIN:

MAY CAUSE IRRITATION, DEFATTING AND DERMATITIS.

### INGESTION:

DO NOT INDUCE VOMITING, KEEP PERSON WARM AND CONSULT A PHYSICIAN IMMEDIATELY.

### INHALATION:

CAN CAUSE NAUSEA AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, HEADACHE AND POSSIBLE UNCONSCIOUSNESS

### HEALTH HAZARDS (ACUTE AND CHRONIC):

EPOXY RESINS CAN CAUSE SENSITIZATION BY EXPOSURE THROUGH CONTACT OR HIGH CONCENTRATIONS OF VAPOR. OVER EXPOSURE TO THIS MATERIAL CAN CAUSE CARDIAC ABNORMALITIES, ANEMIA, LIVER ABNORMALITIES, KIDNEY DAMAGE OR EVEN EYE DAMAGE.

### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS.

### CARCINOGENICITY

OSHA: NO NTP: yes IARC: yes

### ADDITIONAL CARCINOGENICITY INFORMATION:

crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline Silica is also listed by the NTP as a known human carcinogen. Product may contain ethyl benzene as a component of xylene (IARC 2B)

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS NO.	OSHA PEL	ACGIH TLV	OSHA STEL	WEIGHT %
Reaction Products of Epichlorohydrin-Bisphenol A	25068-38-6	NONE	NONE	NONE	40-70
*BUTANOL NORMAL	71-36-3	50PPM	50PPM	NONE	5
Talc	14807-96-6	20mg/m3	20mg/m3	20mg/m3	10-30
*crystalline silica (as a component of talc)	14808-60-7	10mg/m3	.1mg/m3	.1mg/m3	<1.0
*Xylene	1330-20-7	100PPM	100PPM	150PPM	20
*ethyl benzene (as a component of xylene)	100-41-4	100ppm	100ppm	125ppm	0-5.0
*toluene (as a component of xylene)	108-88-3	200ppm	20ppm	150ppm	0-0.2

SECTION 3 NOTES: \*Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372. (ACGIH STEL=150PPM FOR XYLENE). (BUTANOL: OSHA CEILING =50PPM, TWA-SKIN=50PPM, ACGIH TWA SKIN=50PPM). (ETHYL BENZENE ACGIH STEL= 125PPM).

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

## SECTION 4: FIRST AID MEASURES

### EYES:

FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN.

### SKIN:

SKIN CONTACT WILL NORMALLY CAUSE NO MORE THAN IRRITATION BUT WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY.

### INGESTION:

LOW IN TOXICITY, INDUCE VOMITING ONLY IF LARGE AMOUNTS OF MATERIAL ARE INGESTED, AND OTHERWISE DO NOT INDUCE VOMITING. IN EITHER CASE CONSULT WITH A PHYSICIAN.

# SAFETY DATA SHEET

PRODUCT CODE: 2304

## INHALATION:

REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

---

## SECTION 5: FIRE-FIGHTING MEASURES

---

FLAMMABLE LIMITS IN AIR, (% by volume)      UPPER: 11.2%  
   LOWER: 1.4%

FLASH POINT: 88+F

METHOD USED:

SETA FLASH

EXTINGUISHING MEDIA:

FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES:

DO NOT ENTER CONFINED AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL ALL FIRE EXPOSED CONTAINERS WITH WATER. PRESENCE OF SOLVENTS IN PRODUCT MAY REQUIRE GROUNDING.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

IF FIRE OCCURS, SOLVENTS MAY PRODUCE EXCESSIVE PRESSURE. SEALED DRUMS MAY RUPTURE AND IGNITE. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND AND IGNITE BY ANY SOURCE OF IGNITION. NEVER USE A CUTTING OR WELDING TORCH NEAR CONTAINERS (EVEN EMPTY). ALL 5 GALLON AND LARGER CONTAINERS SHOULD BE GROUNDED BEFORE TRANSFERRING MATERIAL.

---

## SECTION 6: RELEASE MEASURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF THE SOURCE AT THE LEAK. REMOVE EXCESS WITH VACUUM TRUCK AND TAKE UP THE REMAINDER WITH AN ABSORBENT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. FLUSH AREA WITH WATER TO REMOVE RESIDUE.

---

## SECTION 7: HANDLING AND STORAGE

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN A COOL DRY PLACE. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS

OTHER PRECAUTIONS:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CAN NOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF. WEAR APPROPRIATE SAFETY EQUIPMENT AND RESPIRATOR AT ALL TIMES WHEN VENTILLATION IS NOT SUFFICIENT TO CONTROL VAPORS.

---

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

---

RESPIRATORY PROTECTION:

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. ENGINEERING OR ADMINISTRATIVE MEASURES SHOULD BE TAKEN TO REDUCE THE RISK AND EXPOSURE.

VENTILATION:

PROVIDE SUFFICIENT MECHANICAL (GENERAL AND LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TOXIC LEVEL VALUES.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCPATIONAL EXPOSURE LIMIT VALUES.

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

APPEARANCE AND ODOR: LOW VISCOSITY LIQUID - AMBER CLEAR - SOLVENT ODOR

BOILING POINT OR RANGE: 200 TO 279F

VAPOR DENSITY (AIR = 1): N/A

SPECIFIC GRAVITY (H2O = 1): 1.2

# SAFETY DATA SHEET

PRODUCT CODE: 2304

EVAPORATION RATE: N/A  
SOLUBILITY IN WATER: NEGLIGIBLE

Odor Threshold: N/A  
pH: N/A  
Melting point/freezing point: N/A  
Vapor Pressure: N/A  
Auto Ignition Temperature: N/A  
Partition Coefficient: n-octanol/water: N/A  
Decomposition Temperature: N/A

---

## SECTION 10: STABILITY AND REACTIVITY

---

### STABILITY:

STABLE

### CONDITIONS TO AVOID (STABILITY):

AVOID EXCESSIVE HEAT OR OPEN FLAMES AS WELL AS ALL SOURCES OF IGNITION SUCH AS SPARKS, HEATERS, AND STATIC DISCHARGES ETC.

### INCOMPATIBILITY (MATERIAL TO AVOID):

AVOID AMINE CURING AGENTS IN UNCONTROLLED AMOUNTS AND STRONG OXIDIZING AGENTS.

### HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

MAY FORM TOXIC CHEMICALS, CARBON DIOXIDE, CARBON MONOXIDE AND VARIOUS HYDROCARBONS ETC

### HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

No data for the product itself.

### Component data:

**Component CAS# 25068-38-6:** Moderate sensitizer, slight eye irritant, moderate skin irritant, Oral LD50 >5000 mg/kg (rat), Dermal LD50 >6000 mg/kg (rabbit)

**Component Butanol CAS# 71-36-3:** Acute Oral Toxicity LD50 = 790 mg/kg (rat) 4hr estimated. Acute Dermal Toxicity LD50 = 3400 mg/kg (rabbit) 4hr estimated. Acute toxicity of the Vapor LC50 = 8000 (rat) 4hr estimated

**Component CAS# 14807-96-6:** Carcinogenic effects – this component may contain crystalline silica dust can cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline Silica is also listed by the NTP as a known human carcinogen

**Component Xylene:** Inhalation LC50 26800ppm, Skin LD50 2000 mg/kg, Ingestion LD50 4.3 g/kg. Exposure may effect skin, eye, liver, kidney, nervous system, respiratory system and lungs. High concentrations may lead to nervous system effects. Repeated overexposure has produced toxic effects in developing and young laboratory animals. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal. Xylene may contain ethyl benzene, and toluene. Ethyl benzene has shown limited evidence of a carcinogenic effect.

**COMPONENT Ethyl Benzene:** Acute Oral toxicity LD50: ca. 3500 mg/kg (rat); Acute inhalation LC50: 17.2 mg/l 4h (rat); Acute Dermal Toxicity: 17,800 mg/kg (rabbit); Skin Irritation rabbit Draize exposure time 24h – slightly irritating. Eye Irritation rabbit Draize – severely irritating. Sensitization dermal (human patch test) non-sensitizer. Repeated Dose toxicity 28 days inhalation NOAEL: 3.4 mg/l (rabbit). Mutagenicity Genetic Toxicity in Vitro: Ames: Negative (salmonella typhimurium, metabolic activation with/without). Carcinogenicity: Ethyl benzene was tested by inhalation exposure in mice and rats. In mice, there was an increased incidence of lung adenomas in males and liver adenomas in females. In male rats, there was an increased incidence of renal tubule adenomas and carcinomas. Two Studies of workers potentially exposed to ethyl benzene in a production plant and a styrene polymerization plant, showed no excess cancer incidence and no excess cancer mortality during a 15 year follow-up. Toxicity to Reproduction/Fertility: Inhalation (monkey, male) Reproductive effects have been observed in animal studies. In a generation study, inhalation (rat/female) NOAEL (parental): 100ppm NOAEL (F2): 100ppm. Developmental Toxicity/Teratogenicity rat, female, inhalation, gestation, daily, NOAEL (teratogenicity): 100ppm (maternal): 100ppm. Teratogenic effects seen only with maternal toxicity. Fetotoxicity seen only with maternal toxicity. Rabbit, female, inhalation, gestation, daily, NOAEL (teratogenicity) < 1000 mg/m3, NOAEL (maternal) < 1000 mg/m3.

---

## SECTION 12: ECOLOGICAL INFORMATION

---

No data for the product itself.

### Component data:

**Component CAS# 25068-38-6:** Biodegradability (Modified Sturm Method) 12%, Fish toxicity: Rainbow trout (96hr) LC50 1.5mg/l, Zebra Fish (96hr) LC50 2.4 mg/l. Invertebrate Toxicity: Daphnia Toxicity (24hr) EC 50 3.6 mg/l

**Component Butanol CAS# 71-36-3:** Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise. The products of degradation are more toxic.

**Component CAS# 14807-96-6:** There is no data that suggests that crystalline silica is toxic to birds, fish, invertebrates, microorganisms or plants.

**Component Xylene:** Acute Toxicity: Fish: Toxic 1 < LCECIC50 < 10mg/l, Aquatic Invertebrates: Toxic 1 < LC/EC/IC50 < 10mg/l, Algae: Toxic 1 < LC/EC/IC50 < 10 mg/l. Mobility – floats on water. If it enters the soil it will be highly mobile and may contaminate groundwater. Oxidizes rapidly by photo-chemical reactions in air.

**COMPONENT Ethyl Benzene:** Biodegradation, Aerobic, 50%, Exposure time 28 days. Biochemical Oxygen demand (BOD) 5 days, 2.8% and 35 days, 1780 mg/g. Bioaccumulation: Cyprinus carpio (Carp), 15 BCF. Acute and Prolonged Toxicity to Fish LC50: 12.1 mg/l (fathead

# SAFETY DATA SHEET

PRODUCT CODE: 2304

minnow, 96 h). Acute Toxicity to Aquatic Invertebrates EC50: 1.8-2.9 mg/l (water flea, 48 h). Toxicity to Aquatic Plants EC50: 4.6 mg/l (green algae, 72 h). Toxicity to microorganisms EC50: 130 mg/l (activated sludge microorganisms, 48 hr).

---

## SECTION 13: WASTE DISPOSAL

---

### WASTE DISPOSAL METHOD:

DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAW.

---

## SECTION 14: Transport Information

---

**DOT:** UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, BUTANOLS), 3, PG III

**IMO/MDG:** UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, BUTANOLS, Bisphenol A Diglycidyl Ether Polymer), 3, PG III, MARINE POLLUTANT

---

## SECTION 15: REGULATORY INFORMATION

---

No data for the product itself.

### Component data:

**Component CAS# 25068-38-6:** Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, WHMIS class D2B; Is on the New Jersey Right to Know list; is on the PA Right to Know List;

**Component Butanol CAS# 71-36-3:** Sara 313 – 40 CFR 372.65 chemical. CERCLA 40 CFR 302.4 (a) Chemical RQ=5000 pounds. On the TSCA list. On the DSL, AICS, ECL, EINECS, and ENCS lists. Butanol is on the Pennsylvania and New Jersey Right to Know lists

**Component CAS# 14807-96-6 may contain** Crystalline Silica (Silicon Dioxide) which is on the TSCA list. NTP list as a known human carcinogen, California proposition 65 list as a known carcinogen, Massachusetts Toxic Use Reduction Act list as toxic, Pennsylvania Worker and community right to know Act list as a hazardous substance.

**Component Xylene:** Xylene contains EPCRA section 313 chemicals subject to the reporting requirements of the emergency planning and community right to know act of 1968. (Maximum wt % for components of xylene are: M-Xylene CAS# 108-38-3 is 46%, P-Xylene CAS# 106-42-3 is 20%, Ethyl Benzene CAS# 100-41-4 is 19%, O-Xylene CAS# 95-47-6 is 16%.. Xylene and its components are on the California Proposition 65 list for developmental toxicity, Reproductive toxicity and carcinogen list. Ingredients are on the TSCA list, DSL Canada, AICS, China, EINECS, ENCS, Korea, New Zealand, Phillipines inventory lists and on the Massachusetts, New Jersey, Pennsylvania right to know lists Ethyl Benzene a component of xylene has been designated by IARC as a possible carcinogen to humans based on increased tumor incidence in laboratory animals. risk phrases R10 Flammable R20/21 Harmful by inhalation and in contact with skin, R38 irritating to skin, S25 Avoid contact with eyes.

**COMPONENT Ethyl Benzene:** US EPA CERCLA Hazardous Substances (40 CFR 302): Ethyl Benzene reportable quantity 1000 lbs. US EPA Emergency Planning and Community Right to Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.5) components, Ethyl Benzene. California Prop 65: This product contains chemicals known to the State of California to be carcinogenic: Ethyl Benzene CAS# 100-41-4 @ 1-5%.

Massachusetts, New York, Pennsylvania Right to Know list includes the following components: Ethyl Benzene CAS# 100-41-4.

Massachusetts, New York, Pennsylvania Special hazardous Substance includes the following components: Ethyl Benzene CAS# 100-41-4

---

## SECTION 16: OTHER INFORMATION

---

**DISCLAIMER:** The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

See Section 1 for date of preparation

# SAFETY DATA SHEET

PRODUCT CODE: 2304

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Oil-Stop Primer Part B  
**PRODUCT CODES:** 2304

**MANUFACTURER:** The Garland Company, Inc.  
**STREET ADDRESS:** 3800 East 91<sup>st</sup>. Street  
**CITY, STATE, ZIP:** Cleveland, Ohio 44105

**The Garland Company, Inc.**  
209 Carrier Drive  
Toronto, Ontario M9W 5Y8



**INFORMATION PHONE:** 800-762-8225  
**EMERGENCY PHONE:** Chemtrec 800-262-8200

**PREPARED BY:** Bill Belardo

**DATE REVISED:** 05-26-15

**Chemical Name or Class:** Polyamide, coal tar and solvent mixture

## SECTION 2: HAZARDS IDENTIFICATION

### Hazard Overview

**GHS Classification:** Carcinogen category 1B, Toxic to reproduction category 1B, Flammable liquid category 3, Specific target organ toxicity following repeated exposure category 2, Skin corrosion/irritation category 1B, skin sensitizer category 1B, Serious eye damage category 1, Germ cell mutagenicity category 2, Acute toxicity inhalation category 4, Acute hazard to aquatic environment category 2, Chronic hazards to aquatic environment category 2

### GHS Label Elements and Precautionary Statements:

**Label Elements:** Flame, Health Hazard, Exclamation Mark, Corrosion, Aquatic Toxicity



### Hazard Statements:

Danger: May Cause cancer  
Warning: Suspected of damaging fertility of the unborn child  
Warning: Flammable liquid and vapor.  
Warning: May cause damage to organs through prolonged or repeated exposure  
Danger: Causes severe skin burns and eye damage  
Warning: May cause an allergic skin reaction  
Danger: Causes severe eye damage  
Warning: Suspected of causing genetic defects  
Warning: Harmful if inhaled  
Toxic to aquatic life  
Toxic to aquatic life with long lasting effects  
Precautionary statements:  
P102 Keep out of reach of children.  
P103 Read label before use  
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray  
P264 Wash hands thoroughly after handling.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P271 Use only outdoors or in a well-ventilated area  
P273 Avoid release to the environment.  
Response;  
P370 + P378 In case of fire: Use FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL for extinction.  
P314 Get medical advice/attention if you feel unwell.  
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.  
P363 Wash contaminated clothing before reuse.



# SAFETY DATA SHEET

PRODUCT CODE: 2304

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.  
P310 Immediately call a POISON CENTER or doctor/physician.  
P321 If skin irritation or burns develop, Call a doctor/physician .  
P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P302 + P352 IF ON SKIN: wash with plenty of soap and water.  
P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.  
P362 + P364 take off contaminated clothing and wash it before reuse  
P310 If in eyes, immediately call a POISON CENTER or doctor/physician.  
P308 + P313 IF exposed or concerned: Get medical advice/attention.  
P312 Call a POISON CENTER or doctor/physician if you feel unwell  
P391 Collect spillage.  
Storage:  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
Disposal:  
P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

## HMIS HAZARD CLASSIFICATION

HEALTH: 3      FLAMMABILITY: 3      REACTIVITY: 0      PERSONAL PROTECTIVE EQUIPMENT: G

## POTENTIAL HEALTH EFFECTS

### EYES:

CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING, OR BLURRED VISION

### SKIN:

MAY CAUSE IRRITATION, DEFATTING AND DERMATITIS.

### INGESTION:

CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, DIARRHEA AND ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

### INHALATION:

CAN CAUSE NAUSEA AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, HEADACHE AND POSSIBLE UNCONSCIOUSNESS

### HEALTH HAZARDS (ACUTE AND CHRONIC):

AMINES CAN CAUSE SENSITIZATION BY EXPOSURE THROUGH CONTACT OR HIGH CONCENTRATIONS OF VAPOR. OVER EXPOSURE TO THIS MATERIAL CAN CAUSE CARDIAC ABNORMALITIES, ANEMIA, LIVER ABNORMALITIES, KIDNEY DAMAGE OR EVEN EYE DAMAGE.

**Coal Tar Pitch Emergency Overview:** (Danger This product is carcinogenic to humans. Repeated or prolonged contact with skin may cause dermatitis and hyperpigmentation of skin. Avoid breathing dust/fume/gas/mist/vapours and sprays. This product is irritating to the eyes, the skin and the respiratory tract. Exposure to sun may enhance the irritating effect of coal tar pitch on skin and eyes and lead to burns. High vapor concentrations may cause dizziness. Use in well-ventilated areas. Avoid prolonged and/or repeated contact including vapors. If appropriate, respiratory protection and other personal protective equipment should be used. ).

### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC RESPONSE

### CARCINOGENICITY

OSHA: YES      NTP: YES      IARC: YES

### ADDITIONAL CARCINOGENICITY INFORMATION:

Product may contain ethyl benzene as a component of xylene (IARC 2B). crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline Silica is also listed by the NTP as a known human carcinogen.

Coal tar: FREQUENT, PROLONGED OR OCCASIONAL BUT INTENSIVE CONTACT WITH THE SKIN OVER A MANY YEAR PERIOD. IN THE ABSENCE OF RECOMMENDED HYGIENE PRACTICES, MAY LEAD TO SKIN PIGMENTATION, BENIGN SKIN GROWTHS AND IN SOME CASES MAY RESULT IN SKIN CANCER. Coal tar pitch is an IARC Group 1 Human carcinogen, an ACGIH A1 Known human carcinogen

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS NO.	OSHA PEL	ACGIH TLV	OSHA STEL	WEIGHT %
*PHENOL	108-95-2	5 PPM	5 PPM	10 PPM	3
BENZYL ALCOHOL	100-51-6	NONE	NONE	NONE	1-5
HEXANEDIAMINE	124-09-4	NONE	NONE	NONE	1-5
1,2 CYCLOHEXANEDIAMINE	694-83-7	NONE	NONE	NONE	1-5
*Xylene	1330-20-7	100PPM	100PPM	150PPM	33
*ethyl benzene (as a component of xylene)	100-41-4	100ppm	100ppm	125ppm	0-5.0
*toluene (as a component of xylene)	108-88-3	200ppm	20ppm	150ppm	0-0.2
NONYL PHENOL	25154-52-3	NONE	NONE	NONE	7-13
Talc	14807-96-6	20mg/m3	20mg/m3	20mg/m3	10-30
*crystalline silica (as a component of talc)	14808-60-7	10mg/m3	.1mg/m3	.1mg/m3	(<1.0%)
TRIS-2,4,6-dimethylaminomethylphenol	90-72-2	NONE	NONE	NONE	1-5
Bis(dimethylaminomethyl) phenol	71074-89-0	NONE	NONE	NONE	0.1-1
1,2-Propanediol	57-55-6	NONE	NONE	NONE	0.1-1

# SAFETY DATA SHEET

PRODUCT CODE: 2304

*Isobutyl Alcohol	78-83-1	50PPM	50PPM	NONE	<0.5%
Salts from alkylamides and esters CAS# Trade secret (NJTSRN 800963-5040)		NONE	NONE	NONE	0.1-1
*COAL TAR PITCH (Crude Coal Tar) (also see section 15 for a chemical list of components contained in the Coal Tar Pitch)	65996-89-6	.2MG/M3	.2MG/M3	NONE	6.2

## SECTION 3 NOTES:

\*\*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.\*\*\*

XYLENE ACGIH STEL=150PPM. ETHYL BENZENE ACGIH STEL=125PPM. REGULATORY STANDARD – NIOSH CRITERIA DOCUMENT, COAL TAR PRODUCTS. USEPA – 40CFR 112

**Note:** Ingredients listed without percentages, the percentages are considered a trade secret.

## SECTION 4: FIRST AID MEASURES

### EYES:

FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN.

### SKIN:

SKIN CONTACT WILL NORMALLY CAUSE NO MORE THAN IRRITATION BUT WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY.

### INGESTION:

DO NOT INDUCE VOMITING, KEEP PERSON WARM AND CONSULT A PHYSICIAN IMMEDIATELY.

### INHALATION:

REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

## SECTION 5: FIRE-FIGHTING MEASURES

**FLAMMABLE LIMITS IN AIR,**  
(% by volume)

**UPPER:** not available

**LOWER:** not available

**FLASH POINT:** 89+F

**METHOD USED:**

SETA FLASH

**EXTINGUISHING MEDIA:**

FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL

### SPECIAL FIRE FIGHTING PROCEDURES:

DO NOT ENTER CONFINED FIRE AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL ALL FIRE EXPOSED CONTAINERS WITH WATER. PRESENCE OF SOLVENTS MAY REQUIRE GROUNDING.

### UNUSUAL FIRE AND EXPLOSION HAZARDS:

IF FIRE OCCURS, SOLVENTS MAY PRODUCE EXCESSIVE PRESSURE. SEALED DRUMS MAY RUPTURE AND IGNITE. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND AND IGNITE BY ANY SOURCE OF IGNITION. NEVER USE A CUTTING OR WELDING TORCH NEAR CONTAINERS (EVEN EMPTY). ALL 5 GALLON AND LARGER CONTAINERS SHOULD BE GROUNDED BEFORE TRANSFERRING MATERIAL.

## SECTION 6: RELEASE MEASURES

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND PROTECTIVE CLOTHING. REMOVE ALL SOURCES OF IGNITIONS. REMOVE EXCESS WITH SPARK PROOF EQUIPMENT AND TAKE UP THE REMAINDER WITH AN ABSORBENT MATERIAL SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. FLUSH AREA WITH WATER TO REMOVE RESIDUE.

## SECTION 7: HANDLING AND STORAGE

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN A COOL DRY PLACE. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS. KEEP MATERIAL AWAY FROM ALL SOURCES OF IGNITION.

### OTHER PRECAUTIONS:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CAN NOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF.

WEAR APPROPRIATE SAFETY EQUIPMENT AND RESPIRATOR AT ALL TIMES WHEN VENTILATION IS NOT SUFFICIENT TO CONTROL VAPORS.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION



# SAFETY DATA SHEET

PRODUCT CODE: 2304

## RESPIRATORY PROTECTION:

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. ENGINEERING OR ADMINISTRATIVE MEASURES SHOULD BE TAKEN TO REDUCE THE RISK AND EXPOSURE.

## VENTILATION:

PROVIDE SUFFICIENT MECHANICAL (GENERAL AND LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TOXIC LEVEL VALUES.

## PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

## EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

## OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

## WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCUPATIONAL EXPOSURE LIMIT VALUES.

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

**APPEARANCE AND ODOR:** BLACK LIQUID WITH SOLVENT ODOR

**BOILING POINT OR RANGE:** 200 TO 560F

**VAPOR DENSITY (AIR = 1):** N/A

**SPECIFIC GRAVITY (H<sub>2</sub>O = 1):** 1.1

**EVAPORATION RATE:** N/A

**SOLUBILITY IN WATER:** NEGLIGIBLE

**Odor Threshold:** N/A

**pH:** N/A

**Melting point/freezing point:** N/A

**Vapor Pressure:** N/A

**Auto Ignition Temperature:** N/A

**Partition Coefficient: n-octanol/water:** N/A

**Decomposition Temperature:** N/A

---

## SECTION 10: STABILITY AND REACTIVITY

---

### STABILITY:

STABLE

### CONDITIONS TO AVOID (STABILITY):

AVOID EXCESSIVE HEAT OR OPEN FLAMES AS WELL AS ALL SOURCES OF IGNITION SUCH AS SPARKS, HEATERS, AND STATIC DISCHARGES ETC.

### INCOMPATIBILITY (MATERIAL TO AVOID):

AVOID EPOXY RESIN AGENTS IN UNCONTROLLED AMOUNTS AND STRONG OXIDIZING AGENTS AS WELL AS STRONG ACIDS.

### HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

MAY FORM TOXIC CHEMICALS, CARBON DIOXIDE, CARBON MONOXIDE AND VARIOUS HYDROCARBONS ETC..

### HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

**Comonent Xylene:** Inhalation LC50 26800ppm, Skin LD50 2000 mg/kg, Ingestion LD50 4.3 g/kg. Exposure may effect skin, eye, liver, kidney, nervous system, respiratory system and lungs. High concentrations may lead to nervous system effects. Repeated overexposure has produced toxic effects in developing and young laboratory animals. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal. Xylene may contain ethyl benzene, and toluene. Ethyl benzene has shown limited evidence of a carcinogenic effect.

**COMPONENT Ethyl Benzene:** Acute Oral toxicity LD50: ca. 3500 mg/kg (rat); Acute inhalation LC50: 17.2 mg/l 4h (rat); Acute Dermal Toxicity: 17,800 mg/kg (rabbit); Skin Irritation rabbit Draize exposure time 24h – slightly irritating. Eye Irritation rabbit Draize – severely irritating. Sensitization dermal (human patch test) non-sensitizer. Repeated Dose toxicity 28 days inhalation NOAEL: 3.4 mg/l (rabbit). Mutagenicity Genetic Toxicity in Vitro: Ames: Negative (salmonella typhimurium, metabolic activation with/without). Carcinogenicity: Ethyl benzene was tested by inhalation exposure in mice and rats. Iln mice, there was an increased incidence of lung adenomas in males and liver adenomas in females. In male rats, there was an increased incidence of renal tubule adenomas and carcinomas. Two Studies of workers potentially exposed to ethyl benzene in a production plant and a styrene polymerization plant, showed no excess cancer incidence and no excess cancer mortality during a 15 year follow-up. Toxicity to Reproduction/Fertility: Inhalation (monkey, male) Reproductive effects have been observed in animal studies, In a generation study, inhalation (rat/female) NOAEL (parental): 100ppm NOAEL (F2): 100ppm. Developmental Toxicity/Teratogenicity rat, female, inhalation, gestation, daily, NOAEL (teratogenicity): 100ppm (maternal): 100ppm. Tratogenetic effects seen only with maternal toxicity., Fetotoxicity seen only with maternal toxicity. Rabbit, female, inhalation, gestation, daily, NOAEL (teratogenicity) < 1000 mg/m3, NOAEL (maternal) < 1000 mg/m3.

# SAFETY DATA SHEET

PRODUCT CODE: 2304

**Component(s):** \*PHENOL CAS# 108-95-2, HEXANEDIAMINE CAS# 124-09-4, 1,2 CYCLOHEXANEDIAMINE CAS# 694-83-7: LD50 >2000 mg/kg (estimated) (rat)

**Component Benxyl Alcohol:** Inhalation LC50 (4hr) >4178 mg/l (rat), Dermal LD50 2000 mg/kg (rabbit) Rats exposed to 800 mg/kg for thirteen weeks exhibited CNS depression and histopathological changes in the brain, thymus and skeletal muscles. The No observed Adverse effect level (NOAEL) was 400 mg/kg. No evidence of carcinogenicity was seen in two year study with rats and mice.

**Component Nonyl Phenol:** Median Lethal Dose Oral: LD50 0.58g/kg (rat) moderately toxic. Dermal LD50 2.14g/kg (rabbit) slightly toxic. Skin Draize Test, rabbit: 500 mg/m3 24hr – corrosive. Eyes Draize test rabbit, 57.00/110 – extremely irritating. Component is a possible risk of impaired fertility.

**Component CAS# 14807-96-6:** Carcinogenic effects – this component may contain crystalline silica dust can cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline Silica is also listed by the NTP as a known human carcinogen

**Component CAS# 90-72-2 and CAS# 71074-89-0:** Oral LD50 (rat) 1200 mg/kg; Dermal LD50 (rabbit) 1280 mg/kg; Inhalation LC50 (rat) > 0.5 mg/liter/1 hour; Severe irritant to eyes of a rabbit. Severe irritant to the skin of a rabbit. Corrosive to the skin of a rabbit.

**Component CAS# 57-55-6:** LD50 = 20000 mg/kg

**Component Isobutyl Alcohol CAS# 78-83-1:** LD50 Dermal (rabbit) = 3400 mg/kg

**COMPONENT COAL TAR PITCH CAS# 65996-89-6:**

The following toxicity data has been determined for Crude Coal Tar by using the information available for its components applied to the guidance on the preparation of an SDS under the requirements of the GHS:

Notes:

- a. No LC50 or LD50 has been established for Crude Coal Tar (as Tar, Coal high temp) as a mixture:
  - Causes respiratory tract irritation
- b. The following Skin Irritation information was found for Crude Coal Tar (as Tar, Coal high temp):
  - Irritating
- c. The following Eye Irritation information was found for Crude Coal Tar (as Tar, Coal high temp):
  - Causes eye irritation
- d. The following Skin Sensitization information was found for Crude Coal Tar (as Tar, Coal high temp):
  - Photosensitizing
- e. No Germ Cell Mutagenicity data available for Crude Coal Tar (as Tar, Coal high temp) as a mixture.
- f. Carcinogenicity: IARC and NTP list Crude Coal Tar (as Tar, Coal high temp) as a category 1A carcinogen. Classified by IARC and the European Commission as a Known Human Carcinogen.

The above toxicity information was determined from available scientific sources to illustrate the prevailing posture of the scientific community. The scientific resources includes: The American Conference of Governmental Industrial Hygienist (ACGIH) Documentation of the Threshold Limit Values (TLVs) and Biological Exposure indices (BEIs) with Other Worldwide Occupational Exposure Values 2009, The International Agency for Research on Cancer (IARC), The National Toxicology Program (NTP) updated documentation, the World Health Organization (WHO) and other available resources, the International Uniform Chemical Information Database (IUCLID), European Union Risk Assessment Report (EU-RAR), Concise International Chemical Assessment Documents (CICAD), European Union Scientific Committee for Occupational Exposure Limits (EU-SCOEL), Agency for Toxic Substances and Disease Registry (ATSDR), Hazardous Substance Data Bank (HSDB), and International Programme on Chemical Safety (IPCS).

---

## SECTION 12: ECOLOGICAL INFORMATION

---

**Component Xylene:** Acute Toxicity: Fish: Toxic 1 < LC/EC/IC50 < 10mg/l, Aquatic Invertebrates: Toxic 1 < LC/EC/IC50 < 10mg/l, Algae: Toxic 1 < LC/EC/IC50 < 10 mg/l. Mobility – floats on water. If it enters the soil it will be highly mobile and may contaminate groundwater. Oxidizes rapidly by photo-chemical reactions in air.

**COMPONENT Ethyl Benzene:** Biodegradation, Aerobic, 50%, Exposure time 28 days. Biochemical Oxygen demand (BOD) 5 days, 2.8% and 35 days, 1780 mg/g. Bioaccumulation: Cyprinus carpio (Carp), 15 BCF. Acute and Prolonged Toxicity to Fish LC50: 12.1 mg/l (fathead minnow, 96 h). Acute Toxicity to Aquatic Invertebrates EC50: 1.8-2.9 mg/l (water flea, 48 h). Toxicity to Aquatic Plants EC50: 4.6 mg/l (green algae, 72 h). Toxicity to microorganisms EC50: 130 mg/l (activated sludge microorganisms, 48 hr).

**Component Benxyl Alcohol:** EC50 (48hr) 400 mg/l Daphnia Magna, EC50 (72hr) 2600 mg/l Algae, Biodegradation BOD<sub>2</sub> 62. Slightly or not bioaccumulative. Toxicity to fish: LC50 (96 hr) 10 mg/l Bluegill sunfish (Lepomis macrochirus), LC50 (96hr) 460 ml/l Fathead minnow (Pimephales promelas), Toxicity to Algae: IC50 (72hr) 700 mg/l

**Component Phenol CAS# 108-95-2:** EC50 (48 hours) 6.6 mg/l (species Daphnia). (low bioaccumulation potential)

**Component Nonyl Phenol:** Ecotoxicity: Daphnia EC50: 0.14-0.44 mg/l, 48 hr. Component is not readily biodegradable, log Pow: 3-4. Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.. Aquatic Toxicity LC50 96 hr, toxicity rating is <0.10 ppm – extremely toxic

**Component CAS# 14807-96-6:** There is no data that suggests that crystalline silica is toxic to birds, fish, invertebrates, microorganisms or plants.

**Component CAS# 90-72-2 and CAS# 71074-89-0:** Toxicity: LC50 fish 447.8 mg/l (96 hr). LC50 Crust 28.2 mg/l (48 hr). EC50 alga 34.8 mg/l (96 hr)

**COMPONENT COAL TAR PITCH CAS# 65996-89-6:**

Ecotoxicity: No data available for the product, Crude Coal Tar as a whole. However, individual components of the product have been found to be toxic to the environment. Liquid may migrate into soil and groundwater and be ingested by wildlife.

Mobility: No data available for the product, Crude Coal Tar as a whole. However, individual components of the product have been found to be absorbed by plants from soil.

---

## SECTION 13: WASTE DISPOSAL

---

### WASTE DISPOSAL METHOD:

DISPOSE OF MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL LAWS.

# SAFETY DATA SHEET

PRODUCT CODE: 2304

## SECTION 14: Transport Information

**DOT:** UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, BUTANOLS, COAL TAR), 3, PG III, MARINE POLLUTANT

**IMO/IMDG:** UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, BUTANOLS, COAL TAR), 3, PG III, MARINE POLLUTANT

## SECTION 15: REGULATORY INFORMATION

No data for the product itself.

### Component data:

**Component Xylene:** Xylene contains EPCRA section 313 chemicals subject to the reporting requirements of the emergency planning and community right to know act of 1968. (Maximum wt % for components of xylene are: M-Xylene CAS# 108-38-3 is 46%, P-Xylene CAS# 106-42-3 is 20%, Ethyl Benzene CAS# 100-41-4 is 19%, O-Xylene CAS# 95-47-6 is 16%.. Xylene and its components are on the California Proposition 65 list for developmental toxicity, Reproductive toxicity and carcinogen list. Ingredients are on the TSCA list, DSL Canada, AICS, China, EINECS, ENCS, Korea, New Zealand, Phillipines inventory lists and on the Massachusetts, New Jersey, Pennsylvania right to know lists Ethyl Benzene a component of xylene has been designated by IARC as a possible carcinogen to humans based on increased tumor incidence in laboratory animals. risk phrases R10 Flammable R20/21 Harmful by inhalation and in contact with skin, R38 irritating to skin, S25 Avoid contact with eyes.

**COMPONENT Ethyl Benzene:** US EPA CERCLA Hazardous Substances (40 CFR 302): Ethyl Benzene reportable quantity 1000 lbs. US EPA Emergency Planning and Community Right to Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.5) components, Ethyl Benzene. California Prop 65: This product contains chemicals known to the State of California to be carcinogenic: Ethyl Benzene CAS# 100-41-4 @ 1-5%.

Massachusetts, New York, Pennsylvania Right to Know list includes the following components: Ethyl Benzene CAS# 100-41-4. Massachusetts, New York, Pennsylvania Special hazardous Substance includes the following components: Ethyl Benzene CAS# 100-41-4

**Component Benxyl Alcohol:** E20/22 Harmful by inhalation and if swallowed. On TSCA list, on DSL Canada

**Component(s): \*PHENOL CAS# 108-95-2, HEXANEDIAMINE CAS# 124-09-4, 1,2 CYCLOHEXANEDIAMINE CAS# 694-83-7:**

Components are on the TSCa Canada DSL, EINECS, AICS, ECL, and PICCS lists.

**Component Phenol CAS# 108-95-2:** EPA Sarah Title III (40CFR 372), Components above the de minimus level.

**Component Nonyl Phenol:** This component is listed on TSCA, EINECS, ACIS, MITI and Canada DSL lists.

**Component CAS# 14807-96-6 may contain** Crystalline Silica (Silicon Dioxide) which is on the TSCA list. NTP list as a known human carcinogen, California proposition 65 list as a known carcinogen, Massachusetts Toxic Use Reduction Act list as toxic, Pennsylvania Worker and community right to know Act list as a hazardous substance.

**Component CAS# 90-72-2 and 71074-89-0** EEC symbol – Harmful, harmful if swallowed (R22) Irritating to eyes and skin (R36/38).

Component is on the Canada DSL, TSCA, EINECS, AICS, ENCS, ECL, SEPA, PICCS lists

**Component CAS# 57-55-6:** Listed on TSCA and DSL

**Component Isobutyl Alcohol CAS# 78-83-1:** Component is on TSCA, EINECS and Canada DSL lists. Section 4 test rules/section 12 export notification for isobutyl alcohol.

**COMPONENT COAL TAR PITCH CAS# 65996-89-6:**

**TSCA:** All components listed or polymer exempt.

This product and/ or its constituents are subject to the following regulations:

OSHA Regulations: OSHA has not established a substance-specific standard for occupational exposure to Crude Coal Tar. However, exposures are regulated under OSHA Air Contaminants Standard (29 CFR1910.1000 Table Z-1) as Coal Tar Pitch Volatiles (CTPV).

**Section 313 Supplier Notification:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372 – AS Marked. The remaining chemicals are Designated hazardous chemicals with reportable quantities.:

CAS #	Chemical Name	Percent by Weight
218-01-9 (40CFR 302.4)	Chrysene,	0.5 – 0.8
56-55-3 (40CFR 302.4)	1,2-Benzanthracene	0.5 – 1.0
50-32-8 (40CFR 302.4)	Benzo(a)pyrene	0.4 – 0.7
205-99-2 (40CFR 302.4)	Benzo(b)Fluoranthene	0.3 – 0.7
132-64-9 (40CFR 302.4)	Dibenzofuran	0.4 – 0.7
83-32-9 (40CFR 302.4)	Acenaphthene	0.4 – 0.8
120-12-7 (SARA 313)	Anthracene	0.7 – 1.0
206-44-0 (40CFR 302.4)	Fluoranthene	1.5 – 2.5
85-01-8 (SARA 313)	Phenanthrene	1 - 3
91-20-3 (SARA 313)	Naphthalene	0.8 – 1.5
53-70-3 (40CFR 302.4)	Dibenz (a,h) anthracene	0.07 – 0.11
193-39-5 (40CFR 302.4)	Indeno (1,2,3-cd) pyrene	0.5 – 1.0
92-52-4 (40CFR 302.4)	Biphenyl	0 – 0.2
Category No. N590	Polycyclic aromatic compounds (PACs)	4.8 – 8.5
129.00.0 (SARA 302) (40CFR 355)	Pyrene	1 – 2

**State Regulations:** The product, **Crude Coal Tar** as a whole is not listed in any state regulations. However, individual components of the product are listed in various state regulations:

• **Pennsylvania Right to Know:** **Crude Coal Tar** as a whole is not listed. However, individual components of the product are listed.

# SAFETY DATA SHEET

PRODUCT CODE: 2304

- **California Prop. 65:** Crude Coal Tar as a whole is not listed. However, individual components of the product are listed.
  - **New Jersey:** Crude Coal Tar as a whole is not listed. However, individual components of the product are listed.
  - **Minnesota:** Crude Coal Tar as a whole is not listed. However, individual components of the product are listed.
  - **Massachusetts:** Crude Coal Tar as a whole is not listed. However, individual components of the product are listed.
- Other regulations:** Crude Coal Tar as a whole may not be listed in other regulations. However, individual components may be listed, check appropriate regulations for further regulatory compliance.
- WHMIS Classification (Canadian):** Crude Coal Tar (listed as Tar Decanter Sludge) is listed as a **D2A**.

---

## SECTION 16: OTHER INFORMATION

---

**DISCLAIMER:** The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

See Section 1 for date of preparation