

## DESCRIPTION

Terra-Lock is a two component, low rise, solvent-free, polyurethane foamable HFO adhesive that contains no high Global Warming Potential (GWP) propellants. The adhesive dispenses rapidly, providing labor savings and fast set-time. It is dispensed in small, foam paddy applications.

## SAFETY

Prior to working with Terra-Lock or any adhesive product, consult product label and Safety Data Sheet (SDS) for necessary health and safety precautions.

## SURFACE PREPARATION

All work surfaces should be clean, dry, and free of dirt, dust, debris or other foreign contaminants.

## STORAGE

Keep temperature of contents between 60°F to 90°F (16°C to 32°C). Bring temperature of material to approximately 70°F (21°C) for approximately 24 hours before use. Do not store in direct sunlight or above 95°F (35°C). Store canisters valve side up. KEEP FROM FREEZING!

## PACKAGING

Terra-Lock is packaged in dual pressurized canisters and dispensed utilizing two, 25-foot hoses, spray foam gun and nozzles. The nozzles change from clear to blue, indicating that the adhesive is too cold and the foam should not be dispensed.

Terra-Lock adhesive kit is available in the following packaging:

### Package Size

Part A Canister - 45.3 lbs.

Part B Canister - 40 lbs.

## LIMITATIONS

- Do not apply to wet surface.
- Do not apply when temperatures are below 40°F (4°C).

| Technical Data                        | Terra-Lock                             |
|---------------------------------------|--|
| <b>Weight</b><br>(includes Packaging) | 45.3 lbs. - Part A<br>40 lbs. - Part B |
| <b>Open Time</b>                      | 1-2 min.                               |
| <b>Work Life in Mixing Nozzle</b>     | 1 min.                                 |
| <b>Time to Full Cure</b>              | 24-48 hours                            |
| <b>Shelf Life</b>                     | 12 months                              |

For specific application recommendations, please contact your local Garland Representative or Garland Technical Service Department.

## TEMPERATURE GUIDELINES

| Technical Data                         | Terra-Lock        |
|--|-------------------|
| <b>Storage Temperature</b>             | 60-90°F (16-32°C) |
| <b>Outside Application Temperature</b> | 40-100°F (4-38°C) |
| <b>Surface Temperature (Substrate)</b> | 40-100°F (4-38°C) |

For more information, visit us at: [www.garlandco.com](http://www.garlandco.com)

**The Garland Company, Inc.**

3800 East 91st Street  
Cleveland, OH 44105  
FAX: 216-641-0633  
Phone: 216-641-7500  
Toll Free: 800-321-9336

**Garland Canada Inc.**

209 Carrier Drive  
Toronto, Ontario  
Canada, M9W 5Y8  
FAX: 416-747-1980  
Phone: 416-747-7995  
Toll Free: 800-387-5991  
(Only in Canada)

Tests verified by independent laboratories. Actual roof performance specifications will vary depending on test speed and temperature. Data reflects samples randomly collected.  $\pm 10\%$  variation may be experienced. The above data supersedes all previously published information. Consult your local Garland Representative or the home office for more information.

Terra-Lock is a trademark of The Garland Company, Inc.