

# SAFETY DATA SHEET

PRODUCT CODE: 2057

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Perma-Top Cove Part A  
**PRODUCT CODES:** 2057

**MANUFACTURER:** The Garland Company, Inc.  
**STREET ADDRESS:** 3800 East 91<sup>st</sup>. Street  
**CITY, STATE, ZIP:** Cleveland, Ohio 44105

The Garland Company, Inc.  
209 Carrier Drive  
Toronto, Ontario M9W 5Y8



**INFORMATION PHONE:** 800-762-8225  
**EMERGENCY PHONE:** Chemtrec 800-262-8200

**PREPARED BY:** Bill Belardo

**DATE REVISED:** 05-26-15

**DATE REVISED:** 4/15/15

**Chemical Name or Class:** Epoxy Mixture

## SECTION 2: HAZARDS IDENTIFICATION

### Hazard Overview

**GHS Classification:** Serious eye damage/Eye irritation category 2A, Skin irritation category 2, skin sensitizer category 1, Long term hazards to aquatic environment Category 2

**GHS Label Elements and Precautionary Statements:**

**Label Elements:** Exclamation Mark, Aquatic Toxicity



### Hazard Statements:

Warning: Causes serious eye irritation.

Warning: Causes skin irritation

Warning: May cause an allergic skin reaction

Toxic to aquatic life with long lasting effects

Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

Response

P302 + P352 IF ON SKIN: wash with plenty of soap and water.

P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 IF eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

Other Non-classifiable potential hazards

Carcinogen category 2

### HMIS HAZARD CLASSIFICATION

**HEALTH:** 1      **FLAMMABILITY:** 1      **REACTIVITY:** 0      **PERSONAL PROTECTIVE EQUIPMENT:** B

### POTENTIAL HEALTH EFFECTS

**EYES:**

**MAY CAUSE IRRITATION BUT NO CORNEAL INJURY IS LIKELY.**

**SKIN:**

**MAY CAUSE IRRITATION OR ALLERGIC SKIN RESPONSE.**

**INGESTION:**

**THIS MATERIAL HAS A PROBABLE LOW ACUTE ORAL TOXICITY.**

# SAFETY DATA SHEET

PRODUCT CODE: 2057

## INHALATION:

NO GUIDE FOR CONTROL KNOWN, HOWEVER, EXPOSURE TO HEATED VAPORS CAN CAUSE IRRITATION TO THE NOSE, THROAT OR MUCOUS MEMBRANES..

## HEALTH HAZARDS (ACUTE AND CHRONIC):

EPOXY RESINS CAN CAUSE SENSITIZATION BY EXPOSURE THROUGH CONTACT OR HIGH CONCENTRATION OF VAPOR. EYES: INJURY IF UNLIKELY BUT STAIN FOR EVIDENCE OF CORNEAL INJURY.

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS.

## CARCINOGENICITY

OSHA: NO NTP: NO IARC: yes

## ADDITIONAL CARCINOGENICITY INFORMATION:

Some colors may contain carbon black - Explanation Of Carcinogenicity: IARC MONOGRAPHS ON EVALUATION OF CARCINOGENIC RISK OF CHEMICALS TO MAN, VOL 65, PG 149, 1996: GROUP 2B. Titanium Dioxide is listed by IARC as possibly carcinogenic to humans (group 2B).

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS NO.	OSHA PEL	ACGIH TLV	OSHA STEL	WEIGHT %
Modified Diglycidyl Ether of Bisphenol A	25068-38-6	NONE	NONE	NONE	60-100
Alkyl Glycidyl Ether	68609-97-2	NONE	NONE	NONE	10-30
(fluoroaliphatic polmeric esters) contains 2-propenoic acid, 2-[Methyl](nonafluorobutyl) sulfonyl]amino]ethyl ester, telomere with mrthyloxirane polymer with oxirane di-2-propenoate and methyloxirane polymer with oxirane mono-prpenoate	1017237-78-3	none	none	none	<0.3%
(fluoroaliphatic polmeric esters) contains 1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4-nonafluoro-n-(2-hydroxyethyl)-N-methyl-	34454-97-2	1mg/m3(skin)	none	none	<0.1%
(fluoroaliphatic polmeric esters) contain 2-propenoic acid, 2-[methyl]nonafluorobutyl)sulfonyl]amino]ethyl ester	67584-55-8	none	none	none	<0.1%
(fluoroaliphatic polmeric esters) contains polyether polymer	NJTSRN 04499600-6437	none	none	none	<0.1%
(fluoroaliphatic polmeric esters) contains 2-methoxymethylethoxypropanol	34590-94-8	600mg/m3(skin)	100ppm	150ppm	<0.1%
(fluoroaliphatic polmeric esters) contain toluene	108-88-3	200ppm	20ppm	300ppm	<0.1%
naphtha, petroleum, heavy	64742-82-1	none	none	none	0.1-1
2-Ethyl-1-Hexanol	104-76-7	NONE	NONE	NONE	0.1-1
*Glycol Ether 2-Butoxyethanol	111-76-2	25PPM	25PPM	NONE	<0.5%
Proprietary Additive-	NJTSRN 800963-5170	NONE	NONE	NONE	0.1-1
Precipitated Silica	112926-00-8	NONE	80mg/m3	NONE	1-5
Colors may contain @ 5-10%:					
Titanium Dioxide	13463-67-7	10mg/m3	10mg/m3	5mg/m3	
*CARBON	1333-86-4	3.5PPM	3.4PPM	NONE	<1.0
Precipitated Silica	112926-00-8	NONE	80mg/m3	NONE	
Iron III oxide	1309-37-1	10mg/m3	5mg/m3	NONE	
Yellow Pigment	Not available	NONE	NONE	NONE	
Zinc Sulfate (component of yellow pigment)	1314-98-3	NONE	NONE	NONE	
Barium Sulfate (component of yellow pigment)	7727-43-7	NONE	NONE	NONE	
Titanium Dioxide (component of yellow pigment)	13463-67-7	NONE	NONE	NONE	
Pigment yellow 65 (component of yellow pigment)	6528-34-3	NONE	NONE	NONE	
Iron III oxide	20344-49-4	15mg/m3	5mg/m3	NONE	
C.I. Pigment Blue	147-14-8	1mg/m3	1mg/m3	NONE	
Aluminum Oxide	1344-28-1	15mg/m3	10mg/m3	NONE	
Silica, amorphous	7631-86-9	80mg/m3	10mg/m3	NONE	
Iron Oxide Yellow	51274-00-1	15mg/m3	10mg/m3	NONE	
Silica, amorphous	7631-86-9	80mg/m3	10mg/m3	NONE	

SECTION 3 NOTES: \*Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372.

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

## SECTION 4: FIRST AID MEASURES

### EYES:

FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN.

### SKIN:

# SAFETY DATA SHEET

PRODUCT CODE: 2057

SKIN CONTACT WILL NORMALLY CAUSE NO MORE THAN IRRITATION BUT WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY.

**INGESTION:**

LOW IN TOXICITY, INDUCE VOMITING ONLY IF LARGE AMOUNTS OF MATERIAL ARE INGESTED, AND OTHERWISE DO NOT INDUCE VOMITING. IN EITHER CASE CONSULT WITH A PHYSICIAN.

**INHALATION:**

REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

**NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:**

---

## SECTION 5: FIRE-FIGHTING MEASURES

---

**FLAMMABLE LIMITS IN AIR,**                      **UPPER:** not available  
(% by volume)                                      **LOWER:** not available

**FLASH POINT:** 200+F

**METHOD USED:**

SETA FLASH

**EXTINGUISHING MEDIA:**

FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

**SPECIAL FIRE FIGHTING PROCEDURES:**

DO NOT ENTER CONFINED FIRE AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL ALL FIRE EXPOSED CONTAINERS WITH WATER.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

NONE KNOWN.

---

## SECTION 6: RELEASE MEASURES

---

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**

WEAR RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF THE SOURCE AT THE LEAK. REMOVE EXCESS WITH VACUUM TRUCK AND TAKE UP THE REMAINDER WITH AN ABSORBENT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. FLUSH AREA WITH WATER TO REMOVE RESIDUE.

---

## SECTION 7: HANDLING AND STORAGE

---

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:**

STORE IN A COOL DRY PLACE. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS

**OTHER PRECAUTIONS:**

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CAN NOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF

---

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

---

**RESPIRATORY PROTECTION:**

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. GENERAL EXHAUST IS USUALLY SUFFICIENT IN LIEU OF NIOSH RESPIRATOR

**VENTILATION :**

GENERAL EXHAUST IS USUALLY SUFFICIENT TO CONTROL VAPORS AND EXPOSURE HAZARDS

**PROTECTIVE GLOVES:**

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

**EYE PROTECTION:**

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:**

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

**WORK HYGIENIC PRACTICES:**

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCPATONAL EXPOSURE LIMIT VALUES

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

**APPEARANCE AND ODOR:** LOW VISCOSITY LIQUID – AMBER COLOR

**BOILING POINT OR RANGE ° F:** 200 TO 375

**VAPOR DENSITY (AIR = 1):** N/A

**SPECIFIC GRAVITY (H2O = 1):** 1.1

# SAFETY DATA SHEET

PRODUCT CODE: 2057

EVAPORATION RATE: N/A  
SOLUBILITY IN WATER: NEGLIGIBLE

Odor Threshold: N/A  
pH: N/A  
Melting point/freezing point: N/A  
Vapor Pressure: N/A  
Auto Ignition Temperature: N/A  
Partition Coefficient: n-octanol/water: N/A  
Decomposition Temperature: N/A

---

## SECTION 10: STABILITY AND REACTIVITY

---

### STABILITY:

STABLE

### CONDITIONS TO AVOID (STABILITY):

AVOID EXCESSIVE HEAT OR OPEN FLAMES.

### INCOMPATIBILITY (MATERIAL TO AVOID):

CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS AND STRONG LEWIS ACIDS OR MINERAL ACIDS.

### HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO<sub>2</sub>, ALDEHYDES, ACIDS. REACTION WITH SOME CURING AGENTS CAN GENERATE LARGE AMOUNTS OF HEAT.

### HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

No data for the product itself.

### Component data:

**Component CAS# 25068-38-6:** Moderate sensitizer, slight eye irritant, moderate skin irritant, Oral LD50 >5000 mg/kg (rat), Dermal LD50 >6000 mg/kg (rabbit)

**Component CAS# 68609-97-2:** possible sensitizer, eye and skin irritant, Oral LD50 >10000 mg/kg (rat), Inhalation LD50 – no microscopic changes

**Component CAS# 64742-82-1:** Acute Oral Toxicity LD50 >5000 mg/kg; Acute Dermal Toxicity LD50 rabbit >3000 mg/kg; Acute inhalation Toxicity LC50 rat >11.6 mg/l; Skin Irritation rabbit – moderate skin irritation.; Eye Irritant – Rabbit.

**Component Carbon:** IARC lists carbon as a possible human carcinogen Category 2B. LD50 – Intravenous, mouse = 440 mg/kg

**Component Titanium Dioxide:** Inhalation 4 h LC50 > 6.82 mg/l; Oral LD50 > 5000 mg/kg, rat; In February 2006, IARC listed titanium dioxide as possibly carcinogenic to humans Group 2B.

**Component CAS# 112926-00-8:** LD50 (rat >5000 mg/kg, LD50 dermal (rat) >2000 mg/kg

---

## SECTION 12: ECOLOGICAL INFORMATION

---

No data for the product itself.

### Component data:

**Component CAS# 25068-38-6:** Biodegradability (Modified Sturm Method) 12%, Fish toxicity: Rainbow trout (96hr) LC50 1.5mg/l, Zebra Fish (96hr) LC50 2.4 mg/l. Invertebrate Toxicity: Daphnia Toxicity (24hr) EC 50 3.6 mg/l

**(fluoroaliphatic polymeric esters)** Ecological information not determined, Chemical fate information not determined.

**Component Titanium Dioxide:** Pimephales promelas (fathead minnow) < 1000 mg/l @ 96h LC50; Pseudokirchneriella subcapitata (green algae) 61 mg/l @ 72h EC50; Daphnia magna (water flea) > 1000 mg/l @ 48h EC50

**Component CAS# 112926-00-8:** Ecotoxicity: EC50 (fish) .10000 mg/l (daphnia >10000 mg/l

---

## SECTION 13: WASTE DISPOSAL

---

### WASTE DISPOSAL METHOD:

DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAW.

---

## SECTION 14: Transport Information

---

DOT: Not Regulated

IMO/IMDG: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PGIII, Marine Pollutant

---

## SECTION 15: REGULATORY INFORMATION

---

No data for the product itself.

### Component data:

**Component CAS# 25068-38-6:** Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, WHMIS class D2B; Is on the New Jersey Right to Know list.; is on the PA Right to Know List;

# SAFETY DATA SHEET

PRODUCT CODE: 2057

**Component CAS# 68609-97-2:** Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, Is on the New Jersey Right to Know list; is on the PA Right to Know List.

**Fluroaliphatic Polymeric Esters:** may contain trace amounts of Section 313 toxic chemicals toluene CAS# 108-88-3. Components on TSCA list or in compliance. Contains chemicals that can cause birth defects or other reproductive harm. The Ingredients are on DSL Canada, Chinas inventory of chemical substances, EINECS, Korean Existing Chemical Inventory Toluene is a California proposition 65 chemical (female reproductive toxin, developmental toxin) This component contains a TSCA section 12(b) chemical (CAS# 1017237-78-3), but is in a quantity less than 0.3%.

**Component CAS# 111-76-2:** Section 313 toxic Chemical. Section 311 hazard category – Chronic fire, On TSCA list. May contain trace components of benzene, toluene, ethylbenzene and NJTSRN 800963-5170 and contains chemicals known to the state of California to cause cancer and birth defects. All components on the DSL Canada

**Component CAS# 64742-82-1** – on TSCA and on Canada DSL

**Component Carbon:** Contains Proposition 65 Chemicals .Carbon: is listed on TSCA and DSL Canada

**Component Titanium Dioxide:** Contains Proposition 65 Chemicals, is on the PA Hazardous substance list, is on the NJ right to know Regulated chemical List.

Titanium Dioxide is on inventory or in compliance with EINECS, TSCA, AICS, DSL, ENCS (JP), KECI (KR), PICCS (PH) and INV (CN).

**Component CAS# 112926-00-8:** Is not classified as dangerous. National Chemical Inventory listings include – AICS, DSL, IECSC, EINECS, ENCS, KECI, NZLOC, PICCS, TSCA,

**Component CAS# 104-76-7:** Component is on the TSCA list and Canada DSL list.

**Component Proprietary Additive-NJTSRN 800963-5170:** Component is non hazardous and is on the TSCA list and Canada DSL list.

---

## SECTION 16: OTHER INFORMATION

---

**DISCLAIMER:** The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

See Section 1 for date of preparation

# SAFETY DATA SHEET

PRODUCT CODE: 2057

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Perma-Top Cove Part B  
**PRODUCT CODES:** 2057

**MANUFACTURER:** The Garland Company, Inc.  
**STREET ADDRESS:** 3800 East 91<sup>st</sup>. Street  
**CITY, STATE, ZIP:** Cleveland, Ohio 44105

The Garland Company, Inc.  
209 Carrier Drive  
Toronto, Ontario M9W 5Y8



**INFORMATION PHONE:** 800-762-8225  
**EMERGENCY PHONE:** Chemtrec 800-262-8200

**PREPARED BY:** Bill Belardo

**DATE REVISED:** 05-26-15

**Chemical Name or Class:** Polyamine mixture

## SECTION 2: HAZARDS IDENTIFICATION

### Hazard Overview

**GHS Classification:** Skin corrosion/irritation category 1, skin sensitizer category 1B, Serious eye damage category 1, Acute hazard to aquatic environment category 3, Chronic hazards to aquatic environment category 2

### GHS Label Elements and Precautionary Statements:

**Label Elements:** Exclamation Mark, Corrosion, Aquatic Toxicity



### Hazard Statements:

Danger: Causes severe skin burns and eye damage

Warning: May cause an allergic skin reaction

Danger: Causes serious eye damage

Harmful to aquatic life

Toxic to aquatic life with long lasting effects

Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use

P260 Do not breathe dust/fume/gas/mist/vapours/spray P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P273 Avoid release to the environment.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P363 Wash contaminated clothing before reuse.

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P321 If skin irritation or burns develop, Call a doctor/physician .

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 If in eyes, immediately call a POISON CENTER or doctor/physician.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

### HMIS HAZARD CLASSIFICATION

**HEALTH:** 2

**FLAMMABILITY:** 1

**REACTIVITY:** 0

**PERSONAL PROTECTIVE EQUIPMENT:** G

### POTENTIAL HEALTH EFFECTS

#### EYES:

**WILL CAUSE BURNS TO EYES. HIGH VAPOR CONCENTRATIONS CAN CAUSE SEVERE IRRITATION TO THE EYES.**

#### SKIN:

**CAN CAUSE SKIN IRRITATION OR POSSIBLE SKIN BURNS**

#### INGESTION:

**LIQUID CAN CAUSE SEVERE DAMAGE TO MUCOUS MEMBRANES IF SWALLOWED.**

#### INHALATION:

# SAFETY DATA SHEET

PRODUCT CODE: 2057

HIGH CONCENTRATIONS OF VAPOR CAN CAUSE IRRITATION TO THE RESPIRATORY TRACT, NAUSEA, AND DIZZINESS.

## HEALTH HAZARDS (ACUTE AND CHRONIC):

PROLONGED OR REPEATED EXPOSURE MAY CAUSE ASTHMA AND SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSES.

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS.

## CARCINOGENICITY

OSHA: NO      NTP: NO      IARC: NO

## ADDITIONAL CARCINOGENICITY INFORMATION:

NO LISTED INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

---

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

---

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
Benzyl Alcohol	100-51-6	NONE	NONE	NONE	30-60
3-Aminomethyl-3,5,5-Trimethyl Cyclohexane	2855-13-2	NONE	NONE	NONE	30-60
2-Hydroxybenzoic Acid	69-72-7	NONE	NONE	NONE	7-13
Precipitated Silica	112926-00-8	NONE	80mg/m3	NONE	1-5

#### SECTION 3 NOTES:

\*\*\*No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.\*\*\*

**Note:** Ingredients listed without percentages, the percentages are considered a trade secret.

---

### SECTION 4: FIRST AID MEASURES

---

#### EYES:

IMMEDIATELY FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES WHILE LIFTING UPPER AND LOWER LIDS. GET IMMEDIATE MEDICAL ASSISTANCE.

#### SKIN:

FLUSH SKIN WITH WATER FOR AT LEAST 15 MINUTES AND REMOVE ALL CONTAMINATED CLOTHING IMMEDIATELY. GET MEDICAL ATTENTION IF REDDENING OR SWELLING OCCURS.

#### INGESTION:

DO NOT INDUCE VOMITING. DILUTE BY GIVING WATER OR MILK TO DRINK IF VICTIM IS CONSCIOUS. GET MEDICAL ATTENTION IMMEDIATELY.

#### INHALATION:

REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

#### NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

---

### SECTION 5: FIRE-FIGHTING MEASURES

---

**FLAMMABLE LIMITS IN AIR,**      **UPPER:** not available  
(% by volume)                      **LOWER:** not available

**FLASH POINT:** 200+F

#### METHOD USED:

SETA FLASH

#### EXTINGUISHING MEDIA:

FOAM, ALCOHOL FOAM, CO2, WATER FOG

#### SPECIAL FIRE FIGHTING PROCEDURES:

TOXIC FUMES WILL BE EVOLVED WHEN THIS MATERIAL IS INVOLVED IN A FIRE. A SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR FIRE FIGHTING. COOL FIRE EXPOSED CONTAINERS WITH WATER.

#### UNUSUAL FIRE AND EXPLOSION HAZARDS:

NONE KNOWN.

---

### SECTION 6: RELEASE MEASURES

---

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

AVOID CONTACT WITH MATERIAL. WEAR THE APPROPRIATE SAFETY EQUIPMENT. STOP SPILL AT SOURCE, DYKE AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. TAKE UP REMAINDER WITH CLAY OR OTHER ABSORBENT AND PLACE IN DISPOSAL CONTAINERS.

---

### SECTION 7: HANDLING AND STORAGE

---

#### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS. RESEAL PARTIALLY USED CONTAINERS. PROPERLY LABEL ALL CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES. OBSERVE CONDITIONS OF GOOD INDUSTRIAL HYGIENE AND SAFE WORKING PRACTICES.

#### OTHER PRECAUTIONS:

MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS OF ALL COMPONENTS TO BECOME FAMILIAR WITH ALL HAZARDS PRIOR TO USING THIS PRODUCT.

---

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

---

**RESPIRATORY PROTECTION:**

NIOSH APPROVED RESPIRATOR PROTECTION REQUIRED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROLS. FOR EMERGENCIES A SELF-CONTAINED BREATHING APPARATUS OR A FULL FACE RESPIRATOR IS RECOMMENDED.

**VENTILATION:**

AVOID BREATHING VAPORS. VENTILATION MUST BE SUFFICIENT TO CONTROL VAPORS.

**PROTECTIVE GLOVES:**

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

**EYE PROTECTION:**

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:**

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

**WORK HYGIENIC PRACTICES:**

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCPATONAL EXPOSURE LIMIT VALUES.

---

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

---

**APPEARANCE AND ODOR:** AMBER CLEAR LIQUID WITH AMINE ODOR

**BOILING POINT OR RANGE ° F:** 401 TO 477

**VAPOR DENSITY (AIR = 1):** N/A

**SPECIFIC GRAVITY (H2O = 1):** 1.0

**EVAPORATION RATE:** N/A

**SOLUBILITY IN WATER:** NEGLIGIBLE

**Odor Threshold:** N/A

**pH:** N/A

**Melting point/freezing point:** N/A

**Vapor Pressure:** N/A

**Auto Ignition Temperature:** N/A

**Partition Coefficient: n-octanol/water:** N/A

**Decomposition Temperature:** N/A

---

**SECTION 10: STABILITY AND REACTIVITY**

---

**STABILITY:**

STABLE

**CONDITIONS TO AVOID (STABILITY):**

AVOID CONTACT WITH OPEN FLAMES AND ALL SOURCES OF IGNITIONS AND SPARKS.

**INCOMPATIBILITY (MATERIAL TO AVOID):**

AVOID CONTACT WITH STRONG OXIDIZING AGENTS MINERAL ACIDS AND EPOXY RESINS IN UNCONTROLLED AMOUNTS.

**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:**

CO, CO2, NOX

**HAZARDOUS POLYMERIZATION:**

WILL NOT OCCUR.

---

**SECTION 11: TOXICOLOGICAL INFORMATION**

---

No data for the product itself.

**Component data:**

**Component Benzyl Alcohol:** Inhalation LC50 (4hr) >4178 mg/l (rat), Dermal LD50 2000 mg/kg (rabbit) Rats exposed to 800 mg/kg for thirteen weeks exhibited CNS depression and histopathological changes in the brain, thymus and skeletal muscles. The No observed Adverse effect level (NOAEL) was 400 mg/kg. No evidence of carcinogenicity was seen in two year study with rats and mice.

**Component CAS# 2855-13-2:** Oral LD50 rat 1030 mg/kg, Skin irritation – Corrosive sucategory 1C where responses occur after exposures between 1 hour and 4 hours and observations up to 14 days. Eye irritation – Risk of serious damage to eyes. Product Sensitization (Magnusson- Kingman test) guinea pig: may cause sensitization by skin contact. Product Teratogenicity oral rat NOEL (no observed effect level) 250 mg/kg

**Component CAS# 69-72-7:** Acute Oral Toxicity LD50 (rat) = 891 mg/kg (behavioral somnolence (general depressed activity, Behavioral muscle weakness)). Acute Inhalation LC50 (rat) >900 mg/m3, 1 hr. Acute Dermal LD50 (rabbit) >10,000 mg/kg. Skin Irritation (rabbit) – mild skin irritation -24hr. Eye Irritation (rabbit) – severe eye irritation.

**Component CAS# 112926-00-8:** LD50 (rat >5000 mg/kg, LD50 dermal (rat) >2000 mg/kg

---

**SECTION 12: ECOLOGICAL INFORMATION**

---



# SAFETY DATA SHEET

PRODUCT CODE: 2057

No data for the product itself.

**Component data:**

**Component Benzyl Alcohol:** EC50 (48hr) 400 mg/l Daphnia Magna, EC50 (72hr) 2600 mg/l Algae, Biodegradation BOD<sub>2</sub> 62. Slightly or not bioaccumulative. Toxicity to fish: LC50 (96 hr) 10 mg/l Bluegill sunfish (*Lepomis macrochirus*), LC50 (96hr) 460 ml/l Fathead minnow (*Pimephales promelas*), Toxicity to Algae: IC50 (72hr) 700 mg/l

**Component CAS# 2855-13-2:** Biodegradability 42% and is not readily biodegradable. Bioaccumulation: - no significant accumulation of the substance in organisms is to be expected. Mobility: The soil mobility of the substance is only minimally affected by adsorption to soil components. Toxicity to fish: LC50 *Lepomis idus* 110 mg/l (96hr). Toxicity to Daphnia NOEC 3 mg/l (504hr). EC50 Daphnia magna 23 mg/l (48 hr). ErC50 *scenedesmus subspicatus* 50 mg/l (72 hr). NOEC *scenedesmus subspicatus* 1.5 mg/l (72 hr). Toxicity to bacteria: EC10 *Pseudomonas putida* 1120 mg/l (18 hr).

**Component CAS# 69-72-7:** Toxicity to Fish LC50 (*Leuciscus idus* – 96 mg/l. Toxicity to Daphnia magna – 105mg/l, 24 hr. Component Mutagenic Effects: Mutagenic for bacteria and/or yeast. Developmental toxicity: Classified reproductive system toxin/female, development toxin possible.

**Component CAS# 112926-00-8:** Ecotoxicity: EC50 (fish) .10000 mg/l (daphnia >10000 mg/l)

---

## SECTION 13: WASTE DISPOSAL

---

**WASTE DISPOSAL METHOD:**

DISPOSE OF MATERIAL AS A HAZARDOUS WASTE ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS.

---

## SECTION 14: Transport Information

---

**DOT:** UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE), 8, PG III

**IMO/IMDG:** UN1760, CORROSIVE LIQUID N.O.S. (CONTAINS ISOPHORONE DIAMINE, BENZYL ALCOHOL), 8, PG III, MARINE POLLUTANT

---

## SECTION 15: REGULATORY INFORMATION

---

No data for the product itself.

**Component data:**

**Component Benzyl Alcohol:** E20/22 Harmful by inhalation and if swallowed. On TSCA list, on DSL Canada

**Component CAS# 2855-13-2:** Acute health hazard. Ingredients on TSCA. International Chemical status listed/registered – EINECS/ELINCS, DSL, AICS, MITI, TCOL, PICCS, China, New Zealand.

**Component CAS# 69-72-7:** Component is on the Pennsylvania and New Jersey right to know lists. Component is on the TSCA and Canada DSL lists.

**Component CAS# 112926-00-8:** Is not classified as dangerous. National Chemical Inventory listings include – AICS, DSL, IECSC, EINECS, ENCS, KECI, NZLOC, PICCS, TSCA,

---

## SECTION 16: OTHER INFORMATION

---

**DISCLAIMER:** The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

See Section 1 for date of preparation

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Perma-Top Cove Part C  
**PRODUCT CODES:** 2057

**MANUFACTURER:** The Garland Company, Inc.  
**STREET ADDRESS:** 3800 East 91<sup>st</sup>. Street  
**CITY, STATE, ZIP:** Cleveland, Ohio 44105

The Garland Company, Inc.  
209 Carrier Drive  
Toronto, Ontario M9W 5Y8



**INFORMATION PHONE:** 800-762-8225  
**EMERGENCY PHONE:** Chemtrec 800-262-8200

**PREPARED BY:** Bill Belardo

**DATE REVISED:** 05-26-15

**Chemical Name or Class:** sand

## SECTION 2: HAZARDS IDENTIFICATION

### Hazard Overview

**GHS Classification:** Carcinogenicity category 1, Specific target organ toxicity following repeated exposure category 1, Specific target organ toxicity (single exposure) category 3

### GHS Label Elements and Precautionary Statements:

Label Elements: Health hazard, Exclamation Mark



### Hazard Statements:

DANGER: May cause cancer  
DANGER: Causes damage to organs through prolonged or repeated exposures (lungs, respiratory system)  
WARNING: May cause respiratory irritation.

### Precautionary statements:

P102 Keep out of reach of children.  
P103 Read label before use  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P280 Wear protective gloves/protective clothing/eye protection/face protection  
P260 Do not breathe dust/fume/gas/mist/vapours/spray. P264 Wash hands thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray P271 Use only outdoors or in a well-ventilated area.

### Response:

P308 + P313 IF exposed or concerned: Get medical advice/attention.  
P314 Get medical advice/attention if you feel unwell  
P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.  
P312 Call a POISON CENTER or doctor/physician if you feel unwell.

### Storage:

P405 Store locked up  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

### Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

### HMIS HAZARD CLASSIFICATION

**HEALTH: 2**      **FLAMMABILITY: 0**      **REACTIVITY: 0**      **PERSONAL PROTECTIVE EQUIPMENT: E**

### POTENTIAL HEALTH EFFECTS

#### EYES:

**MAY CAUSE REDDENING OF THE EYES OR EYE IRRITATION FROM AIRBORNE PARTICLES.**

#### SKIN:

**NONE KNOWN**

#### INGESTION:

**NONE KNOWN**

# SAFETY DATA SHEET

PRODUCT CODE: 2057

## INHALATION:

PROLONGED EXPOSURE TO RESPIRABLE CRYSTALLINE QUARTZ MAY CAUSE DELAYED LUNG INJURY (SILICOSIS). ACUTE OR RAPIDLY DEVELOPING SILICOSIS MAY OCCUR IN A SHORT PERIOD OF TIME IN HEAVY EXPOSURE IN SOME APPLICATIONS SUCH AS SAND BLASTING.

## HEALTH HAZARDS (ACUTE AND CHRONIC):

MAY CAUSE DELAYED SILICOSIS OR RAPID SILICOSIS IN SOME OCCUPATIONS SUCH AS SANDBLASTING, SILICOSIS IS A FORM OF A DISABLING PULMONARY FIBROSIS WHICH CAN BE PROGRESSIVE AND COULD LEAD TO DEATH. INHALATION MAY LEAD TO LUNG SCARRING AND MASSIVE FIBROSIS WHICH COULD BE ACCOMPANIED BY RIGHT HEART ENLARGEMENT, HEART FAILURE, OR PULMONARY FAILURE, SMOKING AGGRAVATES THE EFFECTS OF EXPOSURE.

## MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS CAN BE AGGRAVATED BY EXPOSURE

## CARCINOGENICITY

OSHA: NO            NTP: YES            IARC: YES

## ADDITIONAL CARCINOGENICITY INFORMATION:

IARC HAS DETERMINED THAT CRYSTALLINE SILICA INHALED IN THE FORM OF QUARTZ IS CARCINOGENIC TO HUMANS (GROUP 1- CARCINOGENIC TO HUMANS). THE NTP CLASSIFIES RESPIRABLE CRYSTALLINE SILICA AS REASONABLY ANTICIPATED TO BE A CARCINOGEN.

---

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

---

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
SILICON DIOXIDE	14808-60-7	10mg/m3	.1mg/m3	.1mg/m3	100

## SECTION 2 NOTES:

\*\*\*No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.\*\*\*

FOLLOW OSHA HAZARD COMMUNICATION RULE 29CFR SECTIONS 1910.1200, 1915.99, 1917.28, 1918.9, 1926.59, AND STATE AND LOCAL COMMUNITY RIGHT TO KNOW LAWS. WE RECOMMEND THAT SMOKING BE PROHIBITED IN AREAS WHERE RESPIRATORS MUST BE USED.

---

## SECTION 4: FIRST AID MEASURES

---

### EYES:

FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN IF CONDITIONS WARRANT.

### SKIN:

SKIN CONTACT WILL NORMALLY CAUSE NO HEALTH RISKS

### INGESTION:

IF INGESTED, CONSULT A PHYSICIAN

### INHALATION:

REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

### NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

---

## SECTION 5: FIRE-FIGHTING MEASURES

---

FLAMMABLE LIMITS IN AIR,  
(% by volume)

UPPER: not available

LOWER: not available

FLASH POINT<sup>0</sup> F: N/A

METHOD USED:

N/A

EXTINGUISHING MEDIA:

OTHER

SPECIAL FIRE FIGHTING PROCEDURES:

CRYSTALLINE SILICA IS NEITHER A FIRE NOR AN EXPLOSION HAZARD

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NONE KNOWN.

---

## SECTION 6: RELEASE MEASURES

---

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND USE DUSTLESS HANDLING EQUIPMENT TO CLEAN UP LARGE SPILLS, PLACE IN SUITABLE CONTAINERS FOR DISPOSAL. FLUSH AREA WITH WATER AFTER PICKUP OF MATERIAL.

---

## SECTION 7: HANDLING AND STORAGE

---

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN COOL DRY PLACE. PROPERLY LABEL ALL CONTAINERS AND RESEAL ALL PARTIALLY USED CONTAINERS. AVOID CREATING ANY DUST WHEN WORKING WITH THIS MATERIAL.

### OTHER PRECAUTIONS:

# SAFETY DATA SHEET

PRODUCT CODE: 2057

AVOID BREATHING DUST GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. PROVIDE TRAINING FOR YOUR EMPLOYEES RELATING TO OCCUPATIONAL EXPOSURE TO QUARTZ DUST. SEE ASTM STANDARD E1132-86 STANDARD PRACTICE FOR HEALTH REQUIREMENTS RELATING TO EXPOSURE TO QUARTZ DUST. IF BETTER THAN 500 X PEL USE A SELF CONTAINED BREATHING APPARATUS. IF SANDBLASTING, USE ANY TYPE CE SUPPLIED AIR RESPIRATOR WITH FULL FACE PIECE OR HOOD.

## Safety phrases

S22 Do not breathe dust  
S25 Avoid contact with eyes  
S38 In case of insufficient ventilation wear suitable respiratory equipment  
S39 Wear eye/face protection

---

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### RESPIRATORY PROTECTION:

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER-EXPOSURE TO QUARTZ DUST. PROVIDE SUFFICIENT EXHAUST TO KEEP EXPOSURE LEVELS BELOW THE ACGIH PEL.

### VENTILATION:

USE EXHAUST SUFFICIENT TO MAINTAIN AIRBORNE PARTICULATES BELOW THE ACGIH PEL LIMITS ESTABLISHED.

### PROTECTIVE GLOVES:

N/A

### EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

PROVIDE ANY EQUIPMENT NECESSARY TO PREVENT THE INHALATION OF QUARTZ DUST.

### WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCPATIONAL EXPOSURE LIMIT VALUES

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

**APPEARANCE AND ODOR:** WHITE OF TAN SAND GRANULAR CRUSHED OR GROUND- NO ODOR

**BOILING POINT OR RANGE ° F:** N/A

**VAPOR DENSITY (AIR = 1):** N/A

**SPECIFIC GRAVITY (H2O = 1):** 2.6

**EVAPORATION RATE:** N/A

**SOLUBILITY IN WATER:** INSOLUBLE IN WATER

**Odor Threshold:** N/A

**pH:** N/A

**Melting point/freezing point:** N/A

**Vapor Pressure:** N/A

**Auto Ignition Temperature:** N/A

**Partition Coefficient: n-octanol/water:** N/A

**Decomposition Temperature:** N/A

---

## SECTION 10: STABILITY AND REACTIVITY

---

### STABILITY:

STABLE

### CONDITIONS TO AVOID (STABILITY):

CONTACT WITH POWERFUL OXIDIZING AGENTS SUCH AS FLUORINE, CHLORINE, TRIFLUORIDE, MANGANESE TRIOXIDE, OXYGEN TRIFLUORIDE

### INCOMPATIBILITY (MATERIAL TO AVOID):

CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS- SEE CONDITIONS TO AVOID

### HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

SILICA WILL DISSOLVE IN HYDROCHLORIC ACID TO FORM A CORROSIVE GAS- SILICON TETRAFLUORIDE

### HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

Silicon dioxide: Inhalation and retention of respirable crystalline silica can cause silicosis in several forms, chronic, accelerated or acute.

Acute silicosis can occur with exposures to high concentrations of respirable crystalline silica over a very short time period, the symptoms of acute silicosis include progressive shortness of breath, fever, cough, and weight loss. Acute silicosis can be fatal. IARC concluded that there was sufficient evidence in humans for the carcinogenicity of crystalline silica in the form of quartz (Group 1). Exposure to respirable crystalline silica can also be associated with autoimmune disease, tuberculosis, kidney damage, non-malignant respiratory disease. For further information, the NIOSH Hazard Review- Occupational Effects of Occupational Exposure to Respirable Crystalline Silica published in April of 2002 should be reviewed.

---

## SECTION 12: ECOLOGICAL INFORMATION

Silicon Dioxide: There is no data that suggests that crystalline silica is toxic to birds, fish, invertebrates, microorganisms or plants.

---

## SECTION 13: WASTE DISPOSAL

### WASTE DISPOSAL METHOD:

DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAWS.

---

## SECTION 14: Transport Information

**DOT:** Not Regulated

**IMO/MDG** Not regulated

---

## SECTION 15: REGULATORY INFORMATION

Silicon Dioxide: risk phrases: R 48/20 Harmful – Danger of serious damage to health by prolonged exposure through inhalation. Safety Phrases: S 22 – Do not breathe dust and S 38 – In case of insufficient ventilation, wear suitable respiratory equipment

Crystalline Silica (Silicon Dioxide) is on the TSCA list. NTP list as a known human carcinogen, California proposition 65 list as a known carcinogen, Massachusetts Toxic Use Reduction Act list as toxic, Pennsylvania Worker and community right to know Act list as a hazardous substance.

Crystalline Silica (Silicon Dioxide) is on the Canada DSL – WHMIS Classification D2A

Crystalline Silica is on the Australian Inventory of Chemicals Substances list, Japan Ministry of International Trade and Industry list, Korea Existing Chemicals Inventory with registry number 9212-5667 and the Phillipines Inventory of Chemicals and Chemical Substances list.

---

## SECTION 16: OTHER INFORMATION

**DISCLAIMER:** The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

**N/A = Not Available**

See Section 1 for date of preparation