

OVERVIEW & FEATURES

Rust-Go VOC Top Coat is a premium industrial maintenance coating. It is used in conjunction with Metal Roof Primer over properly prepared metal substrates as a durable coating. This product is environmentally friendly, eliminating the flammability and toxicity hazards associated with solvent-based coatings and makes it an excellent choice for use in hotels, schools, nursing homes, hospitals, cafeterias, offices and other areas where odors would be objectionable.

Rust-Go VOC Top Coat is recommended for use on interior and exterior metal and previously painted surfaces. Rust-Go VOC Top Coat exhibits good adhesion to baked enamel and some fluoropolymer coated surfaces.

Durable - Rust-Go VOC Top Coat offers excellent adhesion to aged coatings. It is also resistant to yellowing, mild industrial fumes, and light chemical exposure, making it an ideal choice for restoration projects.

Seals & Conditions - Rust-Go VOC Top Coat protects and preserves facility assets by preventing metal deterioration caused by oxidation and rust.

Versatile - Rust-Go VOC Top Coat is designed to maintain and protect metals from rusting and breaking down. These substrates include metal roofs, equipment on a rooftop, and metal in and around the facility. Rust-Go VOC Top Coat can be tinted to a wide variety of light colors.

APPLICATION

All surfaces must be sound, dry, clean and free of oil, dirt, grease, wax, mildew, loose or flaking paint and rust by scraping, sanding or wire brush or blasting. Check adhesion of old paint using ASTM 3359, measuring adhesion by Tape Method A.

Remove any mildew, wearing protective clothing, gloves and glasses: by washing with a solution of three quarts of warm water, and TSP or Simple Green solution. Rinse thoroughly.

Dull all hard or glossy surfaces by sanding to assure maximum adhesion. Wipe galvanized surfaces clean with mineral spirits prior to application.

This product can be applied by spray, brush or roller. See the spray application guide for spray pump equipment requirements and application tips. For brushing and rolling, use a synthetic brush or roller of appropriate size and/or nap for the surface being painted.

Apply Rust-Go VOC Top Coat over a small area at 0.5 gal/100 sq. ft. (0.21 l/m²) and let set for 20 minutes. Monitor Rust-Go VOC Top Coat to ensure adhesion and note if sag occurs. If any sag occurs, adjust coverage as necessary. Otherwise, proceed with application. Two coats required. Avoid excessive re-brushing or re-rolling.

NOTE: Use soapy water for clean up.

PRECAUTIONS

- Do not apply when the ambient temperature is below 50°F (10°C) or above 90°F (32.2°C) or rain is in the forecast
- Wear protective clothing and chemical splash goggles to avoid contact with eyes
- Avoid prolonged contact with skin and wash thoroughly after handling
- See Safety Data Sheet for additional safety information and specific product analysis
- Coverage rates may vary based on surface condition / texture and do not take into account material loss due to spraying, surface texture, surface absorption, waste, etc.
- To avoid dew point conditions during application, substrate temperature must be at least six Fahrenheit degrees, or three Celsius degrees, above measured dew point temperature and rising.
- Do not apply to metal substrates where the surface temperature is above 140°F (60°C)

RUST-GO™ VOC TOP COAT

Rust-Go VOC Top Coat Technical Data Sheet



Technical Data	Rust-Go VOC Top Coat
Non-Volatile (ASTM D 5201)	50%
Solids by Volume (ASTM D 5201)	33%
Density (ASTM D 1475)	11.3 lbs./gal.
Viscosity @77°F (25°C) (ASTM D 562)	100 KU
Drying Time @ 77°F (25°C); 50% RH To Touch To Recoat	1 hour 3 - 5 hours
Wet Film Thickness @ 0.5 gal./100 sq. ft. (0.21 l/m ²)	8 mils
Color	White #1520 (tinting available) Gray #1522
Shelf Life	12 months
Coverage	0.5 gal / 100 sq. ft. per coat (two coats required) (0.21 l/m ²)
Packaging	5 gal. pail (18.9 l)

Eco-Facts	Rust-Go VOC Top Coat
VOC	< 50 g/L

For specific application recommendations, please contact your local Garland Representative or Garland Technical Service Department.



For more information, visit us at: www.garlandco.com

The Garland Company, Inc.
3800 East 91st Street
Cleveland, OH 44105
FAX: 216-641-0633
Phone: 216-641-7500
Toll Free: 800-321-9336

Garland Canada Inc.
3565 Nashua Drive
Mississauga, ON L4V 1R1
Canada
FAX: 416-747-1980
Phone: 416-747-7995
Toll Free: 800-387-5991
(Only in Canada)

Tests verified by independent laboratories. Actual roof performance specifications will vary depending on test speed and temperature. Data reflects samples randomly collected. A ± 10% variation may be experienced. The above data supersedes all previously published information. Consult your local Garland Representative or Garland Corporate Office for more information.

Wise Product Group is a registered trademark of The Garland Company, Inc.