

# Standard™ Roofing Granules



## OVERVIEW & FEATURES

Garland's Standard Roofing Granules are semi-ceramic coated granules that are broadcast by hand or air assist into cold-applied adhesives or hot asphalt bleedout to produce a durable, reflective roof surface.

## COVERAGE

Approximately 60 lbs. per 100 sq. ft. On applications with hot adhesive, immediately embed the granules into the adhesive; do not allow the asphalt to skin over. On applications with cold process adhesives, allow the adhesive to set up for approximately 5 minutes before broadcasting granules.

Technical Data	Standard Roofing Granules
Packaging	50 lb. bags
Hardness Mohs	6-7
Bulk Density	81-86 lbs./ft <sup>3</sup>
Color	Medium Gray

For more information, visit us at: [www.garlandco.com](http://www.garlandco.com)

**The Garland Company, Inc.**  
3800 East 91st Street  
Cleveland, OH 44105  
FAX: 216-641-0633  
Phone: 216-641-7500  
Toll Free: 800-321-9336

**Garland Canada Inc.**  
209 Carrier Drive  
Toronto, Ontario  
Canada, M9W 5Y8  
FAX: 416-747-1980  
Phone: 416-747-7995  
Toll Free: 800-387-5991  
(Only in Canada)

**The Garland Company UK, LTD**  
Unit 5 Glevum Works, Upton Street  
Gloucester, United Kingdom GL1 4LA  
011 44 1452 330 646 (Outside UK)  
Toll Free: 0800 328 5560 (Only in UK)

Tests verified by independent laboratories. Actual roof performance specifications will vary depending on test speed and temperature. Data reflects samples randomly collected. A ± 10% variation may be experienced. The above data supersedes all previously published information. Consult your local Garland Representative or Garland Corporate Office for more information.