

# Tuff-Coat™ Color Chart

## Standard and Custom Colors



**Tuff-Coat** is a high-performance architectural wall coating used to dampproof and beautify all types of exterior and interior masonry surfaces such as concrete, brick, stucco and exterior insulation finishing systems (EIFS). Tuff-Coat's superior flexibility and versatility provide excellent resistance to dirt pickup and prevents wind-driven rain and moisture from seeping into cracks and causing structural damage to new and existing walls.

This washable wall coating hides rust stains and discolorations to bring life back to your building. But what really sets Tuff-Coat apart is the beauty it adds to all types of exterior and interior masonry surfaces with an extensive line of stunning colors to choose from.

### Standard Colors



Sandstone



White



Gray

*Please note: Variations in screen quality, printers and settings can impact how a color is represented and may differ from the application. This is the most accurate color representation possible.*

**Tuff-Coat Custom Colors** will require up to 3-4 weeks to manufacture plus shipping time for delivery, 50 gallon minimum per color required. To obtain a custom color sample, utilize a 4-digit color code from Sherwin-William's established colors for reference when submitting to Customer Service. Please allow up to 5 days to process Tuff-Coat Custom Color Match plus shipping time for delivery. No refunds or returns of custom color products.



### The Garland Company, Inc.

3800 East 91st Street, Cleveland, OH 44105

Phone: 216-641-7500 | Toll Free: 800-321-9336 | Fax: 216-641-0633

[www.garlandco.com](http://www.garlandco.com)

0924 ©2024 The Garland Company, Inc.