



# Rust-Go® VOC Top Coat Special Color

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: 11/14/2022

Date of issue: 11/11/2021

## SECTION 1: IDENTIFICATION

### Product Identifier

**Product Form:** Mixture

**Product Name:** Rust-Go VOC Top Coat Special Color

**Product Code:** 1525-5UN

### Intended Use of the Product

Coatings and paints, thinners, paint removers. For professional use only.

### Name, Address, and Telephone of the Responsible Party

#### **Manufacturer**

The Garland Company, Inc.  
3800 East 91<sup>st</sup> Street  
Cleveland, Ohio 44105-2197  
T-800-762-8225  
F-216-641-0633  
www.garlandco.com

#### **Supplier**

The Garland Company, Inc.  
3800 East 91<sup>st</sup> Street  
Cleveland, Ohio 44105-2197  
T-800-762-8225  
F-216-641-0633  
www.garlandco.com

Garland Canada, Inc.  
209 Carrier Drive  
Toronto, Ontario M9W 5Y8  
T-416-747-7995  
F-416-747-1980  
www.garlandco.com

### Emergency Telephone Number

**Emergency Number:** 1-800-262-8200 (CHEMTREC)

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the Substance or Mixture

#### **Classification (GHS-US)**

Skin Sens. Cat 1	H317
Germ Cell Mutagenicity Cat 1B	H340
Carc Cat 1B	H350
Aq. Hazard Acute 3	H402
Aq. Hazard Chronic 3	H412

### Label Elements

#### **GHS-US Labeling**

# Rust-Go® VOC Top Coat Special Color

## Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: 11/14/2022

Date of issue: 11/11/2021

### Hazard Pictograms (GHS-US)



### Signal Word (GHS-US)

: Danger

### Hazard Statements (GHS-US)

: H317-May cause an allergic skin reaction

H340- May cause genetic defects

H350-May cause cancer by route of exposure if conclusively proven that no other

: route applies

H402-Harmful to aquatic life

H412- Harmful to aquatic life with long lasting effects

### Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 – Avoid release to the environment

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P308 + P313 - IF exposed or concerned: Get medical advice/attention.

P321 - Specific treatment (see supplemental first aid instructions on this label).

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention.

P363 - Wash contaminated clothing before reuse.

P405 – Store locked up

P501 - Dispose of contents/container to an approved landfill.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Component

Name	Product Identifier	%	Classification (GHS-US)
titanium(IV) oxide	(CAS No) 13463-67-7	10-20	Carc. 2, H351
Pigment Green 26	(CAS No.) 68187-49-5	<1	Carc. 2, H351
Talc	(CAS No.) 14807-96-6	<1	Carc. 2, H351
distillates (petroleum), hydrotreated heavy naphthenic	(CAS No) 64742-52-5	< 1	Carc. 1B, H350
3-iodo-2-propynyl butylcarbamate	(CAS No) 55406-53-6	< 1	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation:dust,mist), H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Solvent naphtha (petroleum), light aromatic	(CAS No) 64742-95-6	<1	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
distillates (petroleum), solvent-dewaxed heavy paraffinic	(CAS No) 64742-65-0	<1	Carc. 1B, H350

## SECTION 4: FIRST AID MEASURES

### First-aid measures general:

IF exposed or concerned: Get medical advice/attention.

# Rust-Go® VOC Top Coat Special Color

## Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: 11/14/2022

Date of issue: 11/11/2021

<b>First-aid measures after inhalation:</b>	Remove person to fresh air and keep comfortable for breathing.
<b>First-aid measures after skin contact:</b>	Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
<b>First-aid measures after eye contact:</b>	Rinse eyes with water as a precaution.
<b>First-aid measures after ingestion:</b>	Call a poison center/doctor/physician if you feel unwell.

## SECTION 5: FIRE-FIGHTING MEASURES

### Extinguishing Media

**Suitable Extinguishing Media:** Water spray. Dry powder. Foam. Carbon dioxide.

### Advice for Firefighters

**Fire Fighting Procedures:** Exercise caution when fighting any chemical fire.

**Protection During Firefighting:** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing dust/fume/gas/mist/vapors/spray.

### Environmental Precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Keep out of waterways.

### Methods and Materials for Containment and Cleaning Up

**For Containment and Cleaning Up:** Dike with inert absorbent material. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. Clean contaminated surface thoroughly. After cleaning, flush away traces with water.

## SECTION 7: HANDLING AND STORAGE

### Precautions for Safe Handling

**General Handling:** Avoid breathing dust, mist or spray. Avoid contact with skin and eyes. Avoid prolonged and repeated contact with skin. Clean contaminated clothing. Do not discharge the waste into the drain. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### Conditions for Safe Storage

**General:** Keep container tightly closed in a dry and well-ventilated place. Keep at temperatures above 0°C.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	ACGIH TLV	OSHA PEL
titanium(IV) oxide	TWA: 1 mg/m <sup>3</sup>	15 mg/m <sup>3</sup>
Talc	TWA: 2 mg/m <sup>3</sup>	20 mppcf See appendix C

### Personal Protective Equipment

**Eye/face Protection :** Tightly fitting safety goggles.

**Skin Protection:** Long sleeved clothing. Protective gloves.

**Respiratory Protection :** No special protective equipment required. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

**Hand Protection:** Wear impervious gloves such as vinyl to minimize contact with skin.



**Environmental Exposure Controls:** No specific controls are needed.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

# Rust-Go® VOC Top Coat Special Color

## Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: 11/14/2022

Date of issue: 11/11/2021

<b>Physical State</b>	: Liquid
<b>Color</b>	: Gray
<b>Odor</b>	: Mild odor
<b>pH</b>	: 9.5
<b>Boiling Point (760 mm Hg)</b>	: 94 - 100 °C
<b>Flash Point – Closed Cup</b>	: > 94 °C
<b>Specific Gravity (H<sub>2</sub>O = 1)</b>	: 1.3234 g/ml
<b>VOC</b>	: <50 g/L Coating VOC

## SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** The product is non-reactive under normal conditions of use, storage and transport.

**Chemical Stability:** Stable under normal conditions.

**Possibility of Hazardous Reactions:** No dangerous reactions known under normal conditions of use.

**Conditions to Avoid:** None under recommended storage and handling conditions.

**Incompatible Materials:** No materials to be especially mentioned.

**Hazardous Decomposition Products:** None under normal use.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

#### Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
distillates (petroleum), solvent-dewaxed heavy paraffinic	> 5000 mg/kg (Rat; Literature study)	> 5000 mg/kg body weight (Rabbit; Literature study)	> 5 mg/l/4h (Rat; Literature study)
titanium(IV) oxide (13463-67-7)	> 2000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))	> 10000 mg/kg (Rabbit; Literature study)	> 6.8 mg/l/4h (Rat; Experimental value)
3-iodo-2-propynyl butylcarbamate CAS #55406-53-6	300-500,Rat; OECD 423: Acute Oral Toxicity – Acute Toxic Class Method; Experimental value	> 2000 mg/kg (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)	0.67 mg/l/4h (Rat; Experimental value)
Talc (14807-96-6)	>5000 mg/kg ; experimental value	>2000 mg/kg ; Experimental study study	>2.1 mg/L air ; experimental value

**Skin corrosion/irritation** : Not classified  
pH: 9.5

**Serious eye damage/irritation** : Not classified  
pH: 9.5

**Respiratory or skin sensitization** : May cause an allergic skin reaction.

**Germ cell mutagenicity** : Not classified

**Carcinogenicity** : May cause cancer (Cancer suspected agent).

#### titanium(IV) oxide (13463-67-7)

IARC group 2B - Possibly carcinogenic to humans

#### Talc (14807-96-6)

IARC group 3 – Not classifiable, 2B - Possibly carcinogenic to humans

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity

Harmful to aquatic life.

# Rust-Go® VOC Top Coat Special Color

## Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: 11/14/2022

Date of issue: 11/11/2021

<b>Titanium(IV) oxide (13463-67-7)</b>	
EC50 Daphnia 1	> 100 mg/l (LC50; Equivalent or similar to OECD 202; 48 h; Daphnia magna; Static system; Fresh water; Weight of evidence)
Threshold limit algae 1	61 mg/l (EC50; Other; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)

<b>3-iodo-2-propynyl butylcarbamate CAS # 55406-53-6</b>	
LC50 fish 1	0.2 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Flow-through system)
EC50 Daphnia 1	0.16 mg/l (EC50; EPA OPP 72-2; 48 h; Daphnia magna; Flow-through system)
LC50 Fish 2	85 mg/l (EPA OPP 72-1, 96 h, Oncorhynchus mykiss, Flow-through system, Salt water, Experimental value, Reaction product)
EC 50 Daphnia 2	60 mg/l (EPA OPP 72-2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Reaction product)
ErC50 (algae)	> 41.3 mg/l (EPA OTS 797.1050, 96 h, Selenastrum capricornutum, Static system, Fresh water, Experimental value, Reaction product)

<b>3-iodo-2-propynyl butylcarbamate CAS # 55406-53-6</b>	
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.
Chemical oxygen demand (COD)	1.15 g O <sub>2</sub> /g substance

<b>3-iodo-2-propynyl butylcarbamate CAS # 55406-53-6</b>	
BCF fish 1	3.3 – 4.5 (BCF)
Log Pow	2.81 (Literature; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

<b>3-iodo-2-propynyl butylcarbamate CAS # 55406-53-6</b>	
Surface tension	0.0691 N/m (158 mg/l)
Log Koc	2.1 (log Koc, Experimental value)

<b>Talc CAS # 14807-96-6</b>	
LC50 fish 1	89581 mg/l (ECOSAR v1.00, 96 h, Pisces, Fresh water, QSAR)

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Recommendations:** Dispose of in accordance with local, state, and federal regulations.

**Unused and Contaminated Product:** Empty containers should be taken for local recycling, recovery or waste disposal.

## SECTION 14: TRANSPORT INFORMATION

### 14.1 In Accordance with DOT

**Proper Shipping Name** : Not regulated

### 14.3 In Accordance with IATA

**Proper Shipping Name** : Not regulated

### 14.4 In Accordance with Mexico

**Proper Shipping Name** : Not regulated

## SECTION 15: REGULATORY INFORMATION

### USA

#### Federal Regulations:

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

# Rust-Go® VOC Top Coat Special Color

## Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: 11/14/2022

Date of issue: 11/11/2021

Titanium (IV) dioxide (13463-67-7), 3-iodo-2-propynyl butylcarbamate (55406-53-6), carbon black (1333-86-4)

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values
3-iodo-2-propynyl butylcarbamate (CAS #: 55406-53-6)	<1%

<b>titanium(IV) oxide CAS # 13463-67-7</b>	
Listed on IARC (International Agency for Research on Cancer)	

### State Regulations:

<b>3-iodo-2-propynyl butylcarbamate CAS # 55406-53-6</b>	
U.S. - New Jersey - Right to Know Hazardous Substance List	
<b>titanium(IV) oxide CAS # 13463-67-7</b>	
U.S. - New Jersey - Right to Know Hazardous Substance List	
<b>Talc CAS #14807-96-6</b>	
U.S. - New Jersey - Right to Know Hazardous Substance List	

### California Proposition 65

WARNING: This product does not contain any substances in their current form known to the state of California to cause cancer, developmental and/or reproductive harm

## **SECTION 16: OTHER INFORMATION**

<b>Revision Date</b>	: November 14, 2022
<b>Other Information</b>	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.
<b>Party Responsible for the Preparation of This Document</b>	: The Garland Company, Inc. 3800 East 91 <sup>st</sup> Street Cleveland, Ohio 44105-2197 T-1800-762-8225 F-216-641-0633

*This information is based on our knowledge as of the Revision Date and is intended to describe the product only for the purposes of health, safety and environmental requirements as of the Revision Date. It should not therefore be construed as guaranteeing any specific property of the product nor as providing any warranty, expressed or implied. The user assumes all responsibility, liability, risk of loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use, or disposal of the product.*