

# KEE-Lock™ Spatter Spray

Membrane Adhesive



## DESCRIPTION

KEE-Lock Spatter Spray is a two component, low rise, solvent-free, polyurethane foamable adhesive that contains no high Global Warming Potential (GWP) propellants. The adhesive dispenses quickly and cures in minutes providing an immediate tight bond and labor savings. KEE-Lock Spatter Spray is packaged in dual pressurized canisters and dispensed utilizing a disposable adhesive applicator assembly and twenty-five-foot hoses. This product is approved for use in all US and Canadian markets that regulate ozone-depleting substances.

## BASIC USE

KEE-Lock Spatter Spray is designed for use as an adhesive for adhering Garland's KEE-Stone FB 60 membrane to the underlying base sheet in a two ply hybrid roof assembly.

It is dispensed in a spatter application using our proprietary dual-purpose static mixer.

## SAFETY

Prior to working with KEE-Lock Spatter Spray or any adhesive product consult product label and Safety Data Sheet (SDS) for necessary health and safety precautions.

## SURFACE PREPARATION

All work surfaces should be clean, dry, and free of dirt, dust, debris, oils, loose and/or embedded gravel, un-adhered coatings, deteriorated membrane and other contaminants that may result in a surface that is not sound or is uneven.

## STORAGE

Keep temperature of contents between 60°F to 90°F (16°C to 32°C). Bring temperature of material to approximately 70°F (21°C) for approximately 24 hours before use. Do not store in direct sunlight or above 95°F (35°C). Store canisters valve side up. KEEP FROM FREEZING! KEE-Lock Spatter Spray has a shelf life of 12 months when stored properly.

## PACKAGING

KEE-Lock Spatter Spray is available in the following packages:

Package Size	Canisters/Pallet
--------------	------------------

Part 1, Canister	36
------------------	----

Part 2, Canister	36
------------------	----

Part 1 and Part 2 canister and packaged in individual labeled boxes. The Part 1 box will contain one applicator, hoses, four dual-purpose static mixers, a wrench, petroleum jelly and a set of gloves.

## LIMITATIONS

- Do not apply to wet surface.
- Do not apply when temperatures are below 40°F (4°C).

Technical Data	KEE-Lock Spatter Spray
Skin Time*	5-8 Minutes
VOC Content	<50 g/L
Coverage Rate Spatter Application	Up to 24 squares per set
Shelf Life	12 months
Color (Foamed Adhesive will appear as a homogeneous light amber color with no streaking or marbling)	Part 1 - Amber Part 2 - Clear

\*Note conditions - i.e. Standard Temperature/Humidity Conditions (70°F / 50% RH)



For more information, visit us at: [www.garlandco.com](http://www.garlandco.com)

### The Garland Company, Inc.

3800 East 91st Street  
Cleveland, OH 44105  
FAX: 216-641-0633  
Phone: 216-641-7500  
Toll Free: 800-321-9336

### Garland Canada Inc.

209 Carrier Drive  
Toronto, Ontario  
Canada, M9W 5Y8  
FAX: 416-747-1980  
Phone: 416-747-7995  
Toll Free: 800-387-5991  
(Only in Canada)

### The Garland Company UK, LTD

Second Way Centre, Second Way  
Avonmouth, Bristol UK BS11 8DF  
Phone: 011 44 1174 401050 (Outside UK)  
Toll Free: 0800 328 5560 (Only in UK)

Tests verified by independent laboratories. Actual performance specifications will vary depending on test speed and temperature. Data reflects samples randomly collected. A ± 10% variation may be experienced. The above data supersedes all previously published information. Consult your local Garland Representative or Garland Corporate Office for more information.

All products are trademarks of The Garland Company, Inc., Garland Canada Inc. and The Garland Company UK, LTD.

© 2023 Garland Industries, Inc.

KLSS 0323