

## Adhesive

# Green-Lock<sup>®</sup> Plus Membrane / Flashing Adhesive

Green-Lock Plus Membrane Adhesive and Green-Lock Plus Flashing Adhesive are used to adhere approved Garland modified bitumen base and cap sheets by squeegee or brush to approved roof substrates.



### Installer Friendly

- Low odor
- Low VOCs
- Quick setting



### System Waterproofing

- Watertight
- Moisture-cured
- No shrinkage after curing



### Versatility

- Compatible with asphalt-based roofing mastics, adhesives, and sealants
- Allows modified bitumen to resist softening and staining
- Resilient



Contains ultra-low VOCs, no solvents and is low odor

100% solids and superior adhesion increases the strength of entire roof assembly

High-performance polymer technology provides impervious waterproofing to the roof assembly



### The Garland Company, Inc.

3800 East 91st Street, Cleveland, OH 44105

Phone: 216-641-7500 | Toll Free: 800-321-9336 | Fax: 216-641-0633

[www.garlandco.com](http://www.garlandco.com)

1124 ©2024 The Garland Company, Inc.

Adhesive

# Green-Lock<sup>®</sup> Plus Membrane / Flashing Adhesive

## Features & Benefits

### Installer Friendly

- Low Odor** Ideal installation for facilities with building occupants.
- Low VOCs** Complies with environmental regulations and standards for safer, greener products.
- Quick-Setting** Moisture-cure technology accelerates peak weatherability allowing for fast, ultimate wind uplift resistance compared to solvent-based adhesives.

### System Waterproofing

- Watertight** High-performance polymer technology provides impervious waterproofing to the roof membrane assembly.
- Moisture-Cured** The moisture-cured polymer reacts with the air moisture to form a strong, resilient rubber.
- Strong Adhesion** 100% solids and superior adhesion increases the strength of the entire roof assembly.

### Versatility

- Protection** Resists softening and staining, therefore protecting the performance, appearance and service life of the roof substrate.
- Resilient** Unique polymer modification enables a wide service temperature range for long-term performance.
- No Shrinkage After Curing** System will remain watertight and the superior adhesion will maintain that strength for years to come.



**Green-Lock<sup>®</sup> Plus**  
A waterproofing adhesive  
used for interply and flood  
coat applications.

## Advantages of Green-Lock Plus Membrane / Flashing Adhesive



Low Odor



Quick-Setting



Watertight



Moisture-Cured



Compatibility



**The Garland Company, Inc.**

3800 East 91st Street, Cleveland, OH 44105

Phone: 216-641-7500 | Toll Free: 800-321-9336 | Fax: 216-641-0633

[www.garlandco.com](http://www.garlandco.com)

1124 ©2024 The Garland Company, Inc.