

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 04/16/2018 Date of issue: 04/16/2018

Version: 1.0

# **SECTION 1: IDENTIFICATION**

**Product Identifier** 

Product Form: Mixture Product Name: Energizer BK

# Product Code: 7341 Intended Use of the Product

Roof Coating/Adhesive. For professional use only.

# Name, Address, and Telephone of the Responsible Party

:

Manufacturer

# Supplier

The Garland Company, Inc. 3800 East 91<sup>st</sup> Street Cleveland, Ohio 44105-2197 T-800-762-8225 F-216-641-0633 www.garlandco.com The Garland Company, Inc. 3800 East 91<sup>st</sup> Street Cleveland, Ohio 44105-2197 T-800-762-8225 F-216-641-0633 www.garlandco.com

Garland Canada, Inc. 209 Carrier Drive Toronto, Ontario M9W 5Y8 T-416-747-7995 F-416-747-1980 www.garlandco.com

#### **Emergency Telephone Number**

Emergency Number : 1-800-762-8225 24 hours

# SECTION 2: HAZARDS IDENTIFICATION

### **Classification of the Substance or Mixture**

Classification (GHS-US) Flam. Liq. 3 H226 Muta. 1B H340 Carc. 1A H350 Repr. 1B H360 Full text of H-phrases: see section 16

### Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)

Signal Word (GHS-US)	: Danger
Hazard Statements (GHS-US)	: H226 - Flammable liquid and vapour
	H340 - May cause genetic defects
	H350 - May cause cancer
	H360 - May damage fertility or the unborn child
Precautionary Statements (GHS-US)	: P201 - Obtain special instructions before use
	P202 - Do not handle until all safety precautions have been read and understood.
	P210 - Keep away from open flames, sparks No smoking.
	P233 - Keep container tightly closed.
	P240 - Ground/bond container and receiving equipment.
	P241 - Use explosion-proof electrical, lighting, ventilating equipment.
	P242 - Use only non-sparking tools.
	P243 - Take precautionary measures against static discharge.
	P280 - Wear protective gloves, eye protection, face protection.
	P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing.
	Rinse skin with water/shower.
	P308+P313 - If exposed or concerned: Get medical advice/attention.
	P370+P378 - In case of fire: Use powder, water spray, foam, carbon dioxide to extinguish.

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 04/16/2018 Date of Issue: 04/16/2018

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to in accordance with local, regional, and national regulations.

### **Other Hazards**

Skin irratation may be aggravated by exposure to sunlight/UV rays.

Unknown Acute Toxicity (GHS-US) Not available

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

<u>Mixture</u>

Name	Product identifier	%	<b>GHS-US classification</b>
asphaltic bitumen, not cut back	(CAS No) 8052-42-4	54.4 - 57.6	Carc. 2, H351
Solvent naphtha (petroleum),	(CAS No) 64742-95-6	25.9 - 31.9	Muta. 1B, H340
light arom., Low boiling point			Carc. 1B, H350
naphtha - unspecified, [A			Asp. Tox. 1, H304
complex combination of			
hydrocarbons obtained from			
distillation of aromatic			
streams. It consists			
predominantly of aromatic			
hydrocarbons having carbon			
numbers predominantly in			
the range of C8 through C10			
and boiling in the range of			
approximately 135°C to			
210°C (275°F to 410°F).]			
1,2,4-trimethylbenzene	(CAS No) 95-63-6	<= 10.208	Flam. Liq. 3, H226
			Acute Tox. 4
			(Inhalation:vapour), H332
			Skin Irrit. 2, H315
			STOT SE 3, H335
			Aquatic Chronic 2, H411
pitch, coal tar, high-temp	(CAS No) 65996-93-2	1.444745 - 7.223725	Muta. 1B, H340
			Carc. 1B, H350
<u></u>			Repr. 1B, H360
Cumene	(CAS No) 98-82-8	<= 0.3509	Flam. Liq. 3, H226
			Carc. 2, H351
			STOT SE 3, H335
			Asp. Tox. 1, H304
cilico	(CAS No) 14808 CO 7	0.135 - 0.21	Aquatic Chronic 2, H411
silica	(CAS No) 14808-60-7	0.135 - 0.21	Carc. 1A, H350
	(CAC No) 10174 11 7	2 115 2 20	STOT RE 1, H372
thickening clay	(CAS No) 12174-11-7	2.115 - 3.29	Carc. 2, H351

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200]. A range of concentration as prescribed by the Controlled Products Regulations has been used where necessary, due to varying composition.

Full text of H-phrases: see section 16

#### Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 04/16/2018 Date of Issue: 04/16/2018

# SECTION 4: FIRST AID MEASURES

# **Description of First Aid Measures**

**General:** Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** Remove person to fresh air and keep comfortable for breathing. Allow victim to breathe fresh air. Allow the victim to rest. **Skin Contact:** Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

Eye Contact: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

# Most Important Symptoms and Effects Both Acute and Delayed

Not expected to present a significant hazard under anticipated conditions of normal use.

# Indication of Any Immediate Medical Attention and Special Treatment Needed

No additional information available.

### SECTION 5: FIRE-FIGHTING MEASURES

# Extinguishing Media

Suitable Extinguishing Media: Foam. Dry powder. Carbon dioxide. Sand. Dry Chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Solid water jet ineffective as extinguishing medium.

# Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable

**Explosion Hazard:** May form flammable/explosive vapour-air mixture.

Reactivity: Product is stable

#### Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Exercise caution when fighting any chemical fire. Treat as a fuel fire. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment. Water and foam may cause frothing.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

#### Hazardous Combustion Products: Not available

## **Reference to Other Sections**

Refer to section 9 for flammability properties.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

#### Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: No open flames. No smoking.

#### For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

#### For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

**Emergency Procedures:** Evacuate unnecessary personnel. Eliminate ignition sources. Stop leak if safe to do so. Ventilate area. Prevent entry to sewers and public waters.

# **Environmental Precautions**

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

#### Methods and Material for Containment and Cleaning Up

For Containment: Dam up the liquid spill.

**Methods for Containment & Cleaning Up:** Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### **Reference to Other Sections**

See heading 8, Exposure Controls and Personal Protection.

### Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 04/16/2018 Date of Issue: 04/16/2018

# SECTION 7: HANDLING AND STORAGE

# Precautions for Safe Handling

Additional Hazards When Processed: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

Hygiene Measures: Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product.

### **Conditions for Safe Storage, Including Any Incompatibilities**

Technical Measures: Ground/bond container and receiving equipment.

**Storage Conditions:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Keep only in the original container in a cool, well ventilated place away from : Heat sources.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

### Specific End Use(s)

Asphalt Roof Primer. For professional use only.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

# **Control Parameters**

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Pitch, coal tar, high-temp (65996-93-2)		
ACGIH	ACGIH TWA (mg/m³)	0.2 mg/m <sup>3</sup>
ACGIH	Remark (ACGIH)	Cancer

Cumene (98-82-8)		
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (ppm)	50 ppm
ACGIH	Remark (ACGIH)	Eye, skin, & URT irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m³)	245 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	50 ppm

1,2,4-Trimethylbenzene (95-63-6)		
ACGIH	ACGIH TWA (ppm)	25 ppm
ACGIH	ACGIH STEL (ppm)	25 ppm

silica (14808-60-7)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup>
OSHA	Remark (OSHA)	(3) See Table Z-3.

#### **Exposure Controls**

Personal Protective Equipment: Avoid all unnecessary exposure. Gloves. Protective clothing. Safety glasses.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

**Eye Protection:** Chemical goggles or safety glasses.

**Skin and Body Protection:** Use of protective creams and sunscreen agents are recommended. Protective creams or "barrier creams" form a film that acts as both a chemical and physical "barrier" between skin and the contaminant and tends to penetration of the contaminant into the pores of the skin. In applying "barrier" creams, be sure the skin is clean and dry. Sunscreen agents filter out most of the rays from the sun.

#### Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 04/16/2018 Date of Issue: 04/16/2018

**Respiratory Protection:** When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**Environmental Exposure Controls:** Do not allow the product to be released into the environment.

**Consumer Exposure Controls:** Do not eat, drink or smoke during use

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Information on Basic Physical and Chemical Properties

Physical State
Appearance
Odor
Flash Point

Solubility

: Liquid

- : A black, thick consistency liquid
- Aromatic Solvent Odor
- : >105°F
- Water: Solubility in water of component(s) of the mixture : cumene: 0.005 g/100ml 1,2,4-trimethylbenzene: 0.0060 g/100ml 1,3- butadiene/styrene,polymer: insoluble silica: insoluble thickening clay: insoluble benzo[a]pyrene: < 0.00001 g/100ml •</li>
   benzo[e]acephenanthrylene: < 0.00001 g/100ml naphthalene: 0.0030 g/100ml phenanthrene: insoluble pyrene: 0.000012 g/100ml dibenz(a,h)anthracene: 0.0000025 g/100ml benzo[a]anthracene: 0.00001 g/100ml fluoranthene: 0.000026 g/100ml dibenz(a,i)pyrene: insoluble chrysene: 0.0000020 g/100ml indeno(1,2,3-cd)pyrene: < 0.00001 g/100ml acenaphthene: insoluble</li>

2B - Possibly carcinogenic to humans, 3 - Not classifiable

# SECTION 10: STABILITY AND REACTIVITY

Reactivity: Product is stable.

Chemical Stability: Not established.

Possibility of Hazardous Reactions: Not established.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures.

Incompatible Materials: Strong acids. Strong bases.

Hazardous Decomposition Products: Fume. Carbon monoxide. Carbon dioxide.

# SECTION 11: TOXICOLOGICAL INFORMATION

Acute toxicity: Not classified

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Not classified

Respiratory or skin sensivitation: May cause an allergic skin reaction.

Germ cell mutagenicity: May cause genetic defects.

Carcinogenicity: May cause cancer.

Pitch, coal tar, high-temp (65996-93-2)

IARC group	1 - Carcinogenic to humans

cumene (98-82-8)		
	IARC group	2B - Possibly carcinogenic to humans

silica (14808-60-7)	
IARC group	1 - Carcinogenic to humans

thickening clay (12174-11-7)
IARC group

asphaltic bitumen, not cut back (8052-42-4)	
IARC group	2A - Probably carcinogenic to humans, 2B - Possibly
	carcinogenic to humans

Safety Data SheetAccording To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And RegulationsRevision Date: 04/16/2018Date of Issue: 04/16/2018

Phenanthrene (85-01-8)	
LD50 oral rat	1800 mg/kg (Rat)
ATE US (oral)	1800.000 mg/kg bodyweight

Fluoranthene (206-44-0)	
LD50 oral rat	2000 mg/kg (Rat)
LD50 dermal rabbit	3180 mg/kg (Rabbit)
ATE US (oral)	2000.000 mg/kg bodyweight
ATE US (dermal)	3180.000 mg/kg bodyweight

Pitch, coal tar, high-temp (65996-93-2)	
LD50 oral rat	> 15000 mg/kg bodyweight (Rat; OECD 401: Acute Oral
	Toxicity; Experimental value)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; Experimental value; OECD
	402: Acute Dermal Toxicity)

Cumene (98-82-8)	
LD50 oral rat	> 2000 mg/kg (Rat; Other; Literature study; 4000 mg/kg
	bodyweight; Rat; Other; Inconclusive, insufficient data)
LD50 dermal rabbit	10578 mg/kg (Rabbit; Literature study; Other)
LC50 inhalation rat (mg/l)	40 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	8000 ppm/4h (Rat; Literature study)
ATE US (dermal)	10578.000 mg/kg bodyweight
ATE US (gases)	8000.000 ppmv/4h
ATE US (vapours)	40.000 mg/l/4h
ATE US (dust,mist)	40.000 mg/l/4h

1,2,4-Trimethylbenzene (95-63-6)	
LD50 oral rat	> 5000 mg/kg (Rat; Equivalent or similar to OECD 401;
	Literature; 6000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 3440 mg/kg (Rat; Read-across; OECD 402: Acute Dermal
	Toxicity)
LC50 inhalation rat (mg/l)	18 mg/l/4h (Rat)
ATE US (vapours)	18.000 mg/l/4h
ATE US (dust, mist)	18.000 mg/l/4h

Reproductive toxicity Specific target organ toxicity (single exposure)	May damage fertility or the unborn child. Not classified
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration hazard	May be fatal if swallowed and enters airways.
Potential adverse human health effects and symptoms	Based on available data, the classification criteria are not met.

### Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 04/16/2018 Date of Issue: 04/16/2018

# **SECTION 12: ECOLOGICAL INFORMATION**

# **Toxicity**

**Ecology - General:** This product may cause adverse environmental effects if used improperly or release to the environment through a spill. Employ best management practices to prevent this material from entering storm sewer systems, waterways or otherwise impacting plant and animal species.

### Persistence and Degradability

Energizer BK	
Persistence and degradability	May cause long-term adverse effects in the environment.

# **Bioaccumulative Potential**

Energizer BK

**Bioaccumulative potential** 

Not established.

Mobility in Soil No additional information available

**Other Adverse Effects** 

Other Information: Avoid release to the environment.

# SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose in a safe manner in accordance with local/national regulations. This product, as supplied, is regulated as a hazardous waste by th U.S. Environmental Protection Agency(EPA) under Resource Conservation and RecoveryAct(RCRA) regulations. If discarded in its purchased form, the product is a RCRA hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or residue of the product remains classified as a hazardous waste as per 40 CFR 261, Subpart C. State or local regulations may also apply if they are differ from federal regulation. RCRA Hazard Class: D001, Ignitable Hazardous Waste. Dispose of contents/container to local/national/international regulations.

**Ecology – Waste Materials:** Avoid release to the environment.

SECTION 14: TRANSPORT	INFORMATION
In Accordance with DOT	
Proper Shipping Name	<ul> <li>Not Regulated when shipped in containers &lt;119 gallons [49 CFR 173.120(b)(2)]. Non-bulk packages are exempt from DOT HM-181 shipping requirements.</li> </ul>
In Accordance with IMDG	
Proper Shipping Name	: Not regulated
In Accordance with IATA	
Proper Shipping Name	: Not regulated
In Accordance with TDG	
Proper Shipping Name	: Not regulated

# **SECTION 15: REGULATORY INFORMATION**

# US Federal Regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

benzo[e]acephenanthrylene	CAS No 205-99-2	0.5879%
dibenzo(a,i)pyrene	CAS No 189-55-9	0.1556%
silica	CAS No 14808-60-7	0.1651%
thickening clay	CAS No 12174-11-7	2.5662%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Cumene (98-82-8)

#### Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 04/16/2018 Date of Issue: 04/16/2018

Listed on United States SARA Section 313

RQ (Reportable quantity, section 304 of EPA's List of Lists) 5	5000 lb
--	---------

# 1,2,4-trimethylbenzene (95-63-6)

Listed on United States SARA Section 313

# **National Regulations**

Pitch, coal tar, high temp. (65996-93-2)
Listed on IARC (International Agency for Research on Cancer)

#### cumene (98-82-8)

Listed on IARC (International Agency for Research on Cancer)

# **US State Regulations**

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

cumene (98-82-8)				
U.S California -	U.S California -	U.S California -	U.S California -	No significance risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -	
		Female	Male	
Yes	No	No	No	

thickening clay (12174-11-7)					
U.S California -	U.S California -	U.S California -	U.S California -	No significance risk level	
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)	
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -		
		Female	Male		
Yes	No	No	No		

# asphaltic bitumen, not cut back (8052-42-4)

U.S. - New Jersey - Right to Know Hazardous Substance List

Pitch, coal tar, high temp. (65996-93-2)		
U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List		

#### cumene (98-82-8)

U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

# 1,2,4-trimethylbenzene (95-63-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

# **Canadian Regulations**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

Energizer BK		
WHMIS Classification	Class B Division 3 - Combustible Liquid	
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

#### Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 04/16/2018 Date of Issue: 04/16/2018



# SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date Other Information

#### : 04/16/2018

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Party Responsible for the Preparation of This Document The Garland Company, Inc. 3800 East 91st Street Cleveland, Ohio 44105-2197 T-800-762-8225

This information is based on our knowledge as of the Revision Date and is intended to describe the product only for the purposes of health, safety, and environmental requirements as of the Revision Date. It should not therefore be construed as guaranteeing any specific property of the product nor as providing any warranty, expressed or implied. The user assumes all responsibility, liability, risk of loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use, or disposal of the product.

North America GHS US 2018 & WHMIS 2