



Tread-Shield VTP

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: N/A

Date of Issue: 12/16/2022

Version: 1.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Tread-Shield VTP A

Product Code: 2011 A

Intended Use of the Product

Primer. For professional use only.

Name, Address, and Telephone of the Responsible Party

Manufacturer

The Garland Company, Inc.
3800 East 91st Street
Cleveland, Ohio 44105-2197
T-800-762-8225
F-216-641-0633
www.garlandco.com

Supplier

The Garland Company, Inc.
3800 East 91st Street
Cleveland, Ohio 44105-2197
T-800-762-8225
F-216-641-0633
www.garlandco.com

The Garland Company, Inc.
209 Carrier Drive
Toronto, Ontario M9W 5Y8
T-416-747-7995 ; 800-387-5991
F-416-747-1980

Emergency Telephone Number

Emergency Number: 1-800-262-8200 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US):

Skin irritation Cat 2
Skin sensitizer Cat 1
Serious eye irritation Cat 2A
Chronic aquatic hazard Cat 2

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Warning

Hazard Statements (GHS-US)

: H315: Causes skin irritation
H319: Causes serious eye irritation
H411: Toxic to aquatic life with long lasting effects

Precautionary Statements (GHS-US)

: P102 Keep out of reach of children.
P103 Read label before use
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P260 Do not breathing dust/fume/gas/mist/vapours/spray
P271 Use only outdoors or in a well-ventilated area.
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P273 Avoid release to the environment.

Response

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

Tread-Shield VTP

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 12/16/2022

P370 + P378 In case of fire: Use Foam, alcohol foam, CO2, dry chemical, water fog for extinction.

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P312 If Inhaled, Call a POISON CENTER or doctor/physician if you feel unwell.

P301 + P312 IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell.

P330 Rinse mouth.

P302 + P352 IF ON SKIN: wash with plenty of soap and water.

P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P280 Wear eye protection/ face protection.

P281 Use personal protective equipment as required.

Response:

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 - Specific treatment (see supplemental first aid instructions on this label).

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

P362 - Take off contaminated clothing and wash before reuse.

P363 - Wash contaminated clothing before reuse.

P391 - Collect spillage.

P501 - Dispose of contents/ container to an approved waste disposal plant.

P337 + P313 IF eye irritation persists: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P233 Keep container tightly closed.

Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component

HAZARDOUS INGREDIENTS:	CAS #	Weight %
Modified Diglycidyl ether of bisphenol A	25068-38-6	30-60
BISPHENOL F/EPICHLOROHYDRIN EPOXY RESIN	9003-36-5	10-30
Alkyl Glycidyl Ether	69609-97-2	5-10

Tread-Shield VTP

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 12/16/2022

Nonyl Phenol	25154-52-3	1-5
Glycidoxypropyl trimethoxysilane	2530-83-8	<1

Composition Comments: Exact concentrations and chemical identities of ingredients not listed above are either classified as non-hazardous or are withheld as a trade secret as covered by OSHA's Hazard Communication Standard, 29 CFR 1910.1200(i).

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: If you feel unwell, seek medical advice (show the label where possible).

Inhalation: Remove victim to fresh air and administer oxygen if necessary

Skin Contact: Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder contaminated clothing before re-use.

Eye Contact: If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention if irritation develops.

Ingestion: Do not induce vomiting, keep person warm and consult an physician immediately.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Foam, alcohol foam, CO2, Dry Chemical, Water, Fog

Advice for Firefighters

Fire Fighting Procedures: Exercise caution when fighting any chemical fire.

Protection During Firefighting: Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray to disperse vapors and protect those stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing includes helmets, protective boots, and gloves will provide a basic level of protection for chemical incidents.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Personal precautions: Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Avoid contact with skin and eyes.

Environmental precautions

Environmental precautions: Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.

Methods and Materials for Containment and Cleaning Up

For Containment: Contain spilled material if possible. Remove all sources of ignition and ventilate the area. Absorb with materials such as: Dirt. Vermiculite. Sand.

Methods for Cleaning Up: Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

Reference to Other Sections: For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

Tread-Shield VTP

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 12/16/2022

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

General Handling: Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink, and animal feed. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Suspected of causing cancer. May damage fertility. May damage the unborn child. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on General Occupational Hygiene: Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.

Conditions for Safe Storage

General: Store away from incompatible materials (see Section 10). Store locked up. Keep only in the original container. Keep container tightly closed in a cool, well ventilated place. Keep containers upright. Protect containers from damage. This product polymerizes when in contact with moisture.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS/GUIDELINES:

HAZARDOUS INGREDIENTS:	CAS #	OSHA PEL	ACGIH TLV	OSHA STEL
Modified Diglycidyl ether of bisphenol A	25068-38-6	None	None	None
BISPHENOL F/EPICHLOROHYDRIN EPOXY RESIN	9003-36-5	None	None	None
Alkyl Glycidyl Ether	69609-97-2	None	None	None
Nonyl Phenol	25154-52-3	None	None	None
Glycidoxypropyl trimethoxysilane	2530-83-8	5 ppm	None	10 ppm

Control Parameters

Occupational Exposure Limits

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above. Use local exhaust ventilation to control airborne vapor. Ensure eyewash/safety shower stations are available near areas where this product is used.

RESPIRATORY PROTECTION: Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

EYE PROTECTION: Safety glasses or chemical goggles as appropriate to prevent eye contact. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

HAND PROTECTION: Use chemical resistant gloves to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

BODY PROTECTION: Use body protection appropriate to prevent contact (e.g. lab coat, overalls). If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards.

Tread-Shield VTP

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 12/16/2022

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

PHYSICAL STATE:	Liquid
APPEARANCE & ODOR:	low viscosity liquid amber clear
ODOR THRESHOLD (PPM):	Not Available
FLASH POINT:	Not Available
AUTOIGNITION TEMPERATURE:	Not Established
VAPOR PRESSURE (mmHg):	Not Available
VAPOR DENSITY:	Not Available
EVAPORATION RATE (nBuAc = 1):	Not Available
BOILING POINT (F°):	200-560
FREEZING POINT (C°):	Not Available
pH:	Not Available
SPECIFIC GRAVITY 20°C: (WATER =1)	Not Available
SOLUBILITY IN WATER (%)	Not Available
EXPLOSIVE PROPERTIES:	Not Available
OXIDISING PROPERTIES:	Not Available

SECTION 10: STABILITY AND REACTIVITY

Reactivity: No additional information available.

Chemical Stability: Stable under recommended storage conditions. See Storage, Section 7.

Possibility of Hazardous Reactions: No potentially hazardous reactions known.

Conditions to Avoid: Avoid excessive heat or open flames as well as all sources of ignition such as sparks, heaters, and static discharges.

Incompatible Materials: Can react vigorously with strong oxidizing agents and phosphorous containing materials.

Hazardous Decomposition Products: Does not decompose when used and stored as recommended. Thermal decomposition may produce harmful gases or vapors.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on Toxicological Effects – Product

CAS# 25068-38-6:
Oral LD50 >5000 mg/kg (rat)
Dermal LD50 >6000 mg/kg (rabbit)

PHENOL, M-XYLENE DIAMINE and Benzene-1, 3-Dimethaneamine/Phenol/ Formaldehyde
Ingestion LD50 > 2200 mg/kg (rat)
Inhalation LC50 (1h) > 20mg/l (rat)
Skin LD50 > 1000 mg/kg (rabbit) all estimated

Tread-Shield VTP

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 12/16/2022

CAS# 68609-97-2

Oral LD50 >10000 mg/kg (rat)

Inhalation LD50 – no microscopic changes

Nonyl Phenol

Median Lethal Dose Oral: LD50 0.58g/kg (rat)

Dermal LD50 2.14g/kg (rabbit)

Skin Draize Test, rabbit: 500 mg/m³ 24hr – corrosive. Eyes Draize test rabbit, 57.00/110 – extremely irritating. Component is a possible risk of impaired fertility.

TOXICITY DATA: Toxicity data is not available for this product:

IRRITANCY OF PRODUCT: Contact with this product can be irritating to exposed skin, eyes, and respiratory system.

SENSITIZATION OF PRODUCT: This product is considered a skin sensitizer.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

25068-38-6

Fish toxicity: Rainbow trout (96hr) LC50 1.5mg/l. Zebra Fish (96hr) LC50 2.4 mg/l

Invertebrate Toxicity: Daphnia Toxicity (24hr) EC 50 3.6 mg/l

Nonyl Phenol

Daphnia EC50: 0.14-0.44 mg/l, 48 hr

Aquatic Toxicity LC50 96 hr, toxicity rating is <0.10 ppm – extremely toxic

Persistence and Degradability

No known applicable information.

Mobility in Soil

Mobility in Soil: No data available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Waste generation should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Unused and Contaminated Product: Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : Not regulated
Hazard Class :
Identification Number :
Packing Group :

14.2 In Accordance with IMDG

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID,
N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer) MARINE
POLLUTANT
Hazard Class : 9
Identification Number : 3082
Packing Group : 3

Tread-Shield VTP

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 12/16/2022

14.3 In Accordance with IATA

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID,
N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer) MARINE
POLLUTANT

Hazard Class : 9

Identification Number : 3082

Packing Group : 3

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

OSHA 29 CFR 1910-1200 – See section 2

TSCA – All components of this product are listed on TSCA Inventory.

CERCLA Reportable Quantity – Not applicable

SARA Title III: Section 302 Extremely Hazardous Substances – None

Section 304 – Not applicable.

Section 311/312 – Acute health and Chronic Health

RCRA – Refer to section 13.

US State Regulations

Component data:

State Right to Know:

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Bisphenol F/epichlorohydrin epoxy resin		X	X		
CAS# 25068-38-6		X	X		
CAS# 68609-97-2			X		
Glycidoxypropyl trimethoxysilane		X	X		

SECTION 16: OTHER INFORMATION

Revision Date : 12/16/2022

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Party Responsible for the Preparation of This Document : The Garland Company, Inc.
3800 East 91st Street
Cleveland, Ohio 44105-2197
T-1800-762-8225
F-216-641-0633

This information is based on our knowledge as of the Revision Date and is intended to describe the product only for the purposes of health, safety and environmental requirements as of the Revision Date. It should not therefore be construed as guaranteeing any specific property of the product nor as providing any warranty, expressed or implied. The user assumes all responsibility, liability, risk of loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use, or disposal of the product.

North America GHS US 2019 & WHMIS

Tread-Shield VTP

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 12/16/2022

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Tread-Shield VTP Part B

Product Code: 2011 B

Intended Use of the Product

Primer. For professional use only.

Name, Address, and Telephone of the Responsible Party

Manufacturer

The Garland Company, Inc.
3800 East 91st Street
Cleveland, Ohio 44105-2197
T-800-762-8225
F-216-641-0633
www.garlandco.com

Supplier

The Garland Company, Inc.
3800 East 91st Street
Cleveland, Ohio 44105-2197
T-800-762-8225
F-216-641-0633
www.garlandco.com

The Garland Company, Inc.
209 Carrier Drive
Toronto, Ontario M9W 5Y8
T-416-747-7995 ; 800-387-5991
F-416-747-1980

Emergency Telephone Number

Emergency Number: 1-800-262-8200 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US):

STOT RE	Cat 2
Skin corrosion	Cat 1B
Skin Sensitizer	Cat 1B
Eye Damage/Irritation	Cat 1
Acute toxicity (inhal)	Cat 4
Germ Cell Mutagen	Cat 2
Reproductive Toxicity	Cat 1B
Acute toxicity (dermal)	Cat 4
Acute aquatic hazard	Cat 2
Chronic aquatic hazard	Cat 2

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Warning

Hazard Statements (GHS-US)

: H315: Causes skin irritation
H319: Causes serious eye irritation
H317: May cause an allergic skin reaction
H335: May cause respiratory irritation
H411: Toxic to aquatic life with long lasting effects

Precautionary Statements (GHS-US)

: P102 Keep out of reach of children.
P103 Read label before use
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.

Tread-Shield VTP

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 12/16/2022

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P260 Do not breathing dust/fume/gas/mist/vapours/spray

P271 Use only outdoors or in a well-ventilated area.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

Response

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P370 + P378 In case of fire: Use Foam, alcohol foam, CO2, dry chemical, water fog for extinction.

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P312 If Inhaled, Call a POISON CENTER or doctor/physician if you feel unwell.

P301 + P312 IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell.

P330 Rinse mouth.

P302 + P352 IF ON SKIN: wash with plenty of soap and water.

P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P280 Wear eye protection/ face protection.

P281 Use personal protective equipment as required.

Response:

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P321 - Specific treatment (see supplemental first aid instructions on this label).

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

P362 - Take off contaminated clothing and wash before reuse.

P363 - Wash contaminated clothing before reuse.

P391 - Collect spillage.

P501 - Dispose of contents/ container to an approved waste disposal plant.

P337 + P313 IF eye irritation persists: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P233 Keep container tightly closed.

Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with

Tread-Shield VTP

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 12/16/2022

local, state, federal or international laws

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component

HAZARDOUS INGREDIENTS:	CAS#	Weight %
Benzyl Alcohol	100-51-6	10-30
1,2-diaminocyclohexane	694-83-7	10-30
Aliphatic amines		10-30
Phenol	108-95-2	3-7
M-xylene diamine	1477-55-0	<2
Benzene-1,3-dimethaneamine/Phenol/Formaldehyde	57214-10-5	0.1-1
Dibutyl Phthalate	84-74-2	15-20

Composition Comments: Exact concentrations and chemical identities of ingredients not listed above are either classified as non-hazardous or are withheld as a trade secret as covered by OSHA's Hazard Communication Standard, 29 CFR 1910.1200(i).

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: If you feel unwell, seek medical advice (show the label where possible).

Inhalation: REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY

Skin Contact: Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder contaminated clothing before re-use.

Eye Contact: If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention if irritation develops. **Ingestion:** DO NOT INDUCE VOMITING, KEEP PERSON WARM AND CONSULT A PHYSICIAN IMMEDIATELY.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Foam, alcohol foam, CO2, Dry Chemical, Water, Fog

Advice for Firefighters

Fire Fighting Procedures: Exercise caution when fighting any chemical fire.

Protection During Firefighting: Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray to disperse vapors and protect those stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing includes helmets, protective boots, and gloves will provide a basic level of protection for chemical incidents.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Personal precautions: Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Avoid contact with skin and eyes.

Environmental precautions

Environmental precautions: Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.

Methods and Materials for Containment and Cleaning Up

Tread-Shield VTP

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 12/16/2022

For Containment: Contain spilled material if possible. Remove all sources of ignition and ventilate the area. Absorb with materials such as: Dirt. Vermiculite. Sand.

Methods for Cleaning Up: Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

Reference to Other Sections: For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

General Handling: Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink, and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Suspected of causing cancer. May damage fertility. May damage the unborn child. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on General Occupational Hygiene: Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.

Conditions for Safe Storage

General: Store away from incompatible materials (see Section 10). Store locked up. Keep only in the original container. Keep container tightly closed in a cool, well ventilated place. Keep containers upright. Protect containers from damage. This product polymerizes when in contact with moisture.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS/GUIDELINES:

HAZARDOUS INGREDIENTS:	CAS #	OSHA PEL	ACGIH TLV	OSHA STEL
Benzyl Alcohol	100-51-6	None	None	None
1,2-diaminocyclohexane	694-83-7	None	None	None
Aliphatic amines		None	None	None
Phenol	108-95-2	5 PPM	5 PPM	10 PPM
M-xylene diamine	1477-55-0	100 PPM	0.1 mg/m ³	125 PPM
Benzene-1,3-dimethanamine/Phenol/Formaldehyde	57214-10-5	None	None	None
Dibutyl Phthalate	84-74-2	5 mg/m ³	5 mg/m ³	5 mg/m ³

Control Parameters

Occupational Exposure Limits

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above. Use local exhaust ventilation to control airborne vapor. Ensure eyewash/safety shower stations are available near areas where this product is used.

Tread-Shield VTP

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 12/16/2022

RESPIRATORY PROTECTION: Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

EYE PROTECTION: Safety glasses or chemical goggles as appropriate to prevent eye contact. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

HAND PROTECTION: Use chemical resistant gloves to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

BODY PROTECTION: Use body protection appropriate to prevent contact (e.g. lab coat, overalls). If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

PHYSICAL STATE:	Liquid
APPEARANCE & ODOR:	Amber clear liquid with amine odor
ODOR THRESHOLD (PPM):	Not Available
FLASH POINT:	Not Available
AUTOIGNITION TEMPERATURE:	Not Established
VAPOR PRESSURE (mmHg):	Not Available
VAPOR DENSITY:	Not Available
EVAPORATION RATE (nBuAc = 1):	Not Available
BOILING POINT (F°):	360-401
FREEZING POINT (C°):	Not Available
pH:	Not Available
SPECIFIC GRAVITY 20°C: (WATER =1)	1.1
SOLUBILITY IN WATER (%):	Not Available
EXPLOSIVE PROPERTIES:	Not Available
OXIDISING PROPERTIES:	Not Available

SECTION 10: STABILITY AND REACTIVITY

Reactivity: No additional information available.

Chemical Stability: Stable under recommended storage conditions. See Storage, Section 7.

Possibility of Hazardous Reactions: No potentially hazardous reactions known.

Conditions to Avoid: Avoid excessive heat or open flames as well as all sources of ignition such as sparks, heaters, and static discharges.

Incompatible Materials: Can react vigorously with strong oxidizing agents and phosphorous containing materials.

Hazardous Decomposition Products: Does not decompose when used and stored as recommended. Thermal decomposition may produce harmful gases or vapors.

SECTION 11. TOXICOLOGICAL INFORMATION

Tread-Shield VTP

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 12/16/2022

Information on Toxicological Effects – Product

Benzyl Alcohol

Inhalation LC50 (4hr) >4178 mg/l (rat),

Dermal LD50 2000 mg/kg (rabbit)

Rats exposed to 800 mg/kg for thirteen weeks exhibited CNS depression and histopathological changes in the brain, thymus and skeletal muscles. The No observed Adverse effect level (NOAEL) was 400 mg/kg. No evidence of carcinogenicity was seen in two year study with rats and mice.

PHENOL, M-XYLENE DIAMINE and Benzene-1, 3-Dimethaneamine/Phenol/ Formaldehyde

Ingestion LD50 > 2200 mg/kg (rat)

Inhalation LC50 (1h) > 20mg/l (rat)

Skin LD50 > 1000 mg/kg (rabbit) all estimated

Phenol

Absorption of phenolic solutions through the skin may be very rapid and can cause death. Lesser exposures can cause damage to the kidneys, liver, pancreas and spleen, and edema to the lungs. Chronic exposures can cause death from liver and kidney damage.

This component has a low bioaccumulation potential.

1,2-benzenedicarboxylic acid, dibutyl ester CAS# 84-74-2

Dibutyl phthalate:

ORAL (LD50): Acute: 7499 mg/kg [Rat]. 3474 mg/kg [Mouse]. 10000 mg/kg [Guinea pig].

DERMAL (LD50): Acute: >20000 mg/kg [Rabbit]. MIST (LC50): Acute: 25000 mg/m² 2 hours [Rat].

Toxicity of the Products of Biodegradation: The products of degradation are less toxic than the product itself.

TOXICITY DATA: Toxicity data is not available for this product:

IRRITANCY OF PRODUCT: Contact with this product can be irritating to exposed skin, eyes, and respiratory system.

SENSITIZATION OF PRODUCT: This product is considered a skin sensitizer.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Specific Component Data:

Benzyl Alcohol

EC50 (48hr) 400 mg/l Daphnia Magna, EC50 (72hr) 2600 mg/l Algae

Biodegradation BOD₂ 62. Slightly or not bioaccumulative

Toxicity to fish: LC50 (96 hr) 10 mg/l Bluegill sunfish (*Lepomis macrochirus*), LC50 (96hr) 460 ml/l Fathead minnow (*Pimephales promelas*), Toxicity to Algae: IC50 (72hr) 700 mg/l

Phenol

Toxicity to Daphnia EC50 (48h) 4.2 mg/l; EC50 (48h) 5.55 mg/l; EC50 (48h) 6.6 mg/l.

This component has a low bioaccumulation potential.

1,2-benzenedicarboxylic acid, dibutyl ester CAS# 84-74-2

Products of Biodegradation: Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are less toxic than the product itself.

Persistence and Degradability

No known applicable information.

Mobility in Soil

Mobility in Soil: No data available

Tread-Shield VTP

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 12/16/2022

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Waste generation should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Unused and Contaminated Product: Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : Corrosive liquid N.O.S. (contains phenol solutions, M-xylene diamine)
Hazard Class : 8
Identification Number : UN 1993
Packing Group : 8

14.2 In Accordance with IMDG

Proper Shipping Name : Corrosive liquid N.O.S. (contains phenol solutions, M-xylene diamine) Marine Pollutant
Hazard Class : 8
Identification Number : UN 1993
Packing Group : 8

14.3 In Accordance with IATA

Proper Shipping Name : Corrosive liquid N.O.S. (contains phenol solutions, M-xylene diamine) Marine Pollutant
Hazard Class : 8
Identification Number : UN 1993
Packing Group : 8

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

OSHA 29 CFR 1910-1200 – See section 2

TSCA – All components of this product are listed on TSCA Inventory.

CERCLA Reportable Quantity – Xylene – 1000 lb RQ

SARA Title III: Section 302 Extremely Hazardous Substances – None

Section 304 – Not applicable.

Section 311/312 – Acute health and Chronic Health

RCRA – Refer to section 13.

US State Regulations

Component data:

State Right to Know:

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
1,2-benzenedicarboxylic acid, dibutyl ester	X		X		

SECTION 16: OTHER INFORMATION

Revision Date : 12/16/2022

Other Information : This document has been prepared in accordance with the SDS

Tread-Shield VTP

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 12/16/2022

Party Responsible for the Preparation of This Document : requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.
The Garland Company, Inc.
3800 East 91st Street
Cleveland, Ohio 44105-2197
T-1800-762-8225
F-216-641-0633

This information is based on our knowledge as of the Revision Date and is intended to describe the product only for the purposes of health, safety, and environmental requirements as of the Revision Date. It should not therefore be construed as guaranteeing any specific property of the product nor as providing any warranty, expressed or implied. The user assumes all responsibility, liability, risk of loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use, or disposal of the product.